



63 A / 80 A / 100 A / 125 A

Main/Emergency-Off Switch ■
Main Switch ■

3 ... 4 pole

IP66 (front)

Four hole mounting 48 × 48 mm

Order code structure:

Ordering example: 4 pole Main/Emergency-Off Switch, 80A, N-padlock device:

Type - Switching programme - Mounting form

H408 - 41400 - 033N4

Type	Rated data (IEC 60947)			Degree of protection Terminals
	Operational current I _o AC-21A (A)	Operational power (at 380–440V) AC-23A (kW) AC-3 (kW)		
H406	63	22	18.5	IP1B
H408	80	30	22	IP1B
H410	100	37	30	IP1B
H412	125	45	37	IP1B

Detailed technical data page 108.

Switching progr.	Poles	Auxiliary contacts	
		n/o	n/c
41300	3	0	0
41311	3	1	1
41320	3	2	0
41400	4	0	0
41411	4	1	1
41420	4	2	0

Switching diagrams and further switching programmes (3 ... 4 pole) page 95.

Mounting form	Operator	Main/Emergency-Off Switch	Mounting form	Operator	Main Switch
033N4	N-padlock device yellow/red	033N1	N-padlock device black		
033M4	M-padlock device yellow/red	033M1	M-padlock device black		
033V4	padlockable with V-handle yellow/red	033V1	padlockable with V-handle silver/black		

Dimensions in mm:

