

# Rittal – The System.

Faster – better – everywhere.

## ► TopTherm fan-and-filter units – SK 3240.124

Date : Sep 14, 2021

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# TopTherm fan-and-filter units – SK 3240.124

created: 14.09.2021 on [www.rittal.com/com-en](http://www.rittal.com/com-en)



## Product description

<b>Protection category IP to IEC 60 529:</b>	IP 54 with standard filter and additional fine filter mat: IP 55 with standard filter and hose-proof hood: IP 56
--	--

<b>Protection category NEMA:</b>	Type 12 with standard filter and additional fine filter mat: Type 12 with standard filter and hose-proof hood: Type 3, 3R, 4, 4X
--------------------------------------	--

<b>Supply includes:</b>	Complete unit ready to install, including filter mat
-------------------------	--

<b>Note:</b>	With the fan-and-filter unit 3237.XXX, electrical connection is made via two single wires (length approx. 300 mm) on the unit, for all other fan-and-filter units, a screwless spring terminal is used
--------------	--

## Product description

<b>Air throughput (unimpeded air flow):</b>	With DC: 180 m <sup>3</sup> /h
---	--------------------------------

<b>Air throughput with outlet filter including standard filter mat (quantity x order number, output 50/60 Hz):</b>	1 x 3240200: 138 m <sup>3</sup> /h 2 x 3240200: 165 m <sup>3</sup> /h 1 x 3243200: 165 m <sup>3</sup> /h
--	--

<b>Rated operating voltage:</b>	24 V (DC)
-------------------------------------	-----------

<b>Dimensions:</b>	Width: 255 mm Height: 255 mm
--------------------	---------------------------------

<b>Required mounting cut-out:</b>	Width: 224 mm Height: 224 mm
---------------------------------------	---------------------------------

<b>Build depth:</b>	25 mm
<b>Installation depth:</b>	107 mm
<b>Temperature range:</b>	Bearing: -30 °C...+70 °C Operation (environment): -30 °C...+55 °C
<b>Power consumption P<sub>el</sub>:</b>	With DC: 10 W
<b>Rated current max.:</b>	With DC: 0.43 A
<b>Miniature circuit- breaker/fuse:</b>	2 A
<b>Service life:</b>	75000 h
<b>Noise level:</b>	With DC: 51 dB(A)
<b>Colour:</b>	RAL 7035
<b>Fan:</b>	Diagonal, DC motor
<b>eCl@ss 8.0/8.1:</b>	27180716
<b>Packs of:</b>	1 pc(s).
<b>Weight/pack:</b>	1.88 kg
<b>EAN:</b>	4028177651968
<b>Customs tariff number:</b>	84145915
<b>ETIM 7.0:</b>	EC000320
<b>ETIM 6.0:</b>	EC000320
<b>eCl@ss 8.0/8.1:</b>	27180716
<b>eCl@ss 6.0/6.1:</b>	27180716
<b>Product description:</b>	SK fan and filter units TopTherm, 180 m <sup>3</sup> /h, 24 V (DC), WHD: 255 x 255 x 25 mm

## Approvals

<b>Approvals:</b>	Approval overview CCC exception letter CSA
-------------------	--

UL + C-UL - FTTA  
UR + C-UR

---

**Certificates:**

EAC

---

**Declarations:**

Declaration of conformity

---