



Main

Range of product	Acti 9
Range	Acti 9
Product name	Acti 9 IHP
Device short name	IHP
Product or component type	Programmable digital time switch
Device application	Building
Battery type	Lithium
Number of channels	1
Provided equipment	Memory key Programming kit
Language	English French German Italian Portuguese Spanish
Colour tint	White (RAL 9003)

Complementary

Power consumption in W	0.4 W
Maximum switching current	16 A - 250 V AC pf = 1 4 A - 250 V AC pf = 0.6
[Ue] rated operational voltage	230 V[Sapce](- 15...10 %) AC 50/60 Hz
Cycle duration	24 hours + 7 days
Maximum number of switchings	56
Minimum interval duration	1 min
Accuracy	+/- 0.5 s/day 25 °C
Display type	LCD
Battery life	10 yr

Backup time	10 years time and program saving
Mounting support	DIN rail
9 mm pitches	2
Function available	Operating hours counter Automatic winter/summer time changeover
Type of setting	Absence for holidays function PIN code
Connections - terminals	Screwless terminals : 2 x 0.5...2.5 mm ²
Width	18 mm
Height	90 mm
Depth	66 mm
Product weight	0.09 kg
Function	None
Absence for holidays	Yes
Time changeover	Automatic
Updated by	None
Compatibility code	IHP
Market segment	Residential Small commercial

Environment

IP degree of protection	IP20 B
Ambient air temperature for operation	-25...55 °C

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1504 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available

Contractual warranty

Warranty period	18 months
-----------------	-----------