

## Synergy® Sleek Design

cooker control units, fused connection units and cable outlets



## Synergy® Sleek Design

hotel equipment



8320 32

8322 37

8324 19

### Sleek design

BSS: Plates made of austenitic Stainless Steel - non-magnetic - grade 304 L

PSS: Plates made of Stainless Steel + rust resistance

G: Plates made of Stainless Steel + rust resistance

Terminal screws captive and backed off ready for cabling - large angled terminal entries

Compact mechanism for maximum wiring space

### Pack Cat.Nos. Cooker control units - 250 V~

Pack	Cat.Nos.	Description
1	8320 29	Conform to BS 4177 : 1992 Flush mounting back box : min. 47 mm deep Nominal plate dimensions : 86 x 146 mm <b>45 A Double pole switch + 13 A DP switched socket outlet - with blue LED power indicator</b> ● Brushed stainless steel
1	8322 29	● Polished stainless steel
1	8324 29	● Gold



### Fused connection units unswitched 13 A - 250 V~

Conform to BS 1363 : Part. 4  
Front cable outlet with cord grip. Fuses supplied  
Locked captive fuse carrier (padlockable)  
Flush mounting back box : min. 35 mm deep  
Supplied with 1 gang side extension  
Cat. No. 8321 98 (3 mm thick) in case of extra wiring space needed  
Nominal plate dimensions : 86 x 86 mm

#### Unswitched - with cord outlet

1	8320 32	● Brushed stainless steel
1	8322 32	● Polished stainless steel
1	8324 32	● Gold



### Fused connection units switched 13 A - 250 V~

Conform to BS 1363 : Part. 4  
Front cable outlet with cord grip. Fuses supplied  
Locked captive fuse carrier (padlockable)  
Flush mounting back box : min. 35 mm deep  
Supplied with 1 gang side extension  
Cat. No. 8321 98 (3 mm thick) in case of extra wiring space needed  
Nominal plate dimensions : 86 x 86 mm

#### Double pole switched - without cord outlet

1	8320 35	● Brushed stainless steel
1	8322 35	● Polished stainless steel
1	8324 35	● Gold



#### Double pole switched - with blue LED power indicator + cord outlet

1	8320 37	● Brushed stainless steel
1	8322 37	● Polished stainless steel
1	8324 37	● Gold



### Cable outlets

Conform to BS 5733  
Fitted with clamp and outlet membrane  
With terminal block  
Nominal plate dimensions : 86 x 86 mm

#### 20 A - 250 V~

1	8320 19	● Brushed stainless steel
1	8322 19	● Polished stainless steel
1	8324 19	● Gold



#### 45 A - 250 V~

1	8320 26	● Anthracite grey colour (plastic)
---	---------	------------------------------------



8320 90

8323 00

8325 01

### Sleek design

BSS: Plates made of austenitic Stainless Steel - non-magnetic - grade 304 L

PSS: Plates made of Stainless Steel + rust resistance

G: Plates made of Stainless Steel + rust resistance

Terminal screws captive and backed off ready for cabling - large angled terminal entries

Compact mechanism for maximum wiring space

### Pack Cat.Nos. Shaver sockets

Pack	Cat.Nos.	Description
1	8320 90	Conform to BS EN 61558-2-5 Suitable for use with European, British, American and Australian 2 pin plugs. Rating: 20 VA. IP 24 Screwless live and neutral terminals Flush mounting back box : min. 45 mm deep Supplied with 2 gang side extension Cat. No. 8321 99 (3 mm thick) in case of extra wiring space needed Nominal plate dimensions : 146 x 86 mm <b>230 V / 120 V - 50/60 Hz</b> ● Brushed stainless steel
1	8322 90	● Polished stainless steel
1	8324 90	● Gold



### Key card switch 230 V

For energising a circuit by inserting a key fob or a smart card (access card for a hotel room)  
Example of use : hotel room power supply only when guest is present  
Time delay of approx. 30 sec. after card removal  
To be equipped with a single pole latching relay or contactor

1	8321 00	● Brushed stainless steel
1	8323 00	● Polished stainless steel
1	8325 00	● Gold



### Hotel call indicator DND/Please clean

Indicator for corridor  
Indicator lamp and bell push  
Installed in the corridor, displays calls  
● Brushed stainless steel  
● Polished stainless steel  
● Gold

1	8321 01	● Brushed stainless steel
1	8323 01	● Polished stainless steel
1	8325 01	● Gold



### Hotel call indicator - internal room control

Internal control unit  
Allows the user to select the desired setting  
Supplied with LED  
● Brushed stainless steel  
● Polished stainless steel  
● Gold

1	8321 02	● Brushed stainless steel
1	8323 02	● Polished stainless steel
1	8325 02	● Gold



# Synergy® Sleek Design

telephone, data sockets and television sockets



# Synergy® Sleek Design

blanking plates, cord outlets



8320 50

8322 54

8324 57



8320 40

8322 41

8324 43

Sleek design

BSS: Plates made of austenitic Stainless Steel - non-magnetic - grade 304 L

PSS: Plates made of Stainless Steel + rust resistance

G: Plates made of Stainless Steel + rust resistance

Terminal screws captive and backed off ready for cabling - large angled terminal entries

Compact mechanism for maximum wiring space

Pack	Cat.Nos.	Telephone sockets
		Flush mounting back box : min. 35 mm deep Nominal plate dimensions : 86 x 86 mm
		<b>UK master</b>
1	8320 50	● Brushed stainless steel
1	8322 50	● Polished stainless steel
1	8324 50	● Gold
		<b>UK secondary</b>
1	8320 51	● Brushed stainless steel
1	8322 51	● Polished stainless steel
1	8324 51	● Gold
		<b>RJ 11 / RJ 12 - single</b>
1	8320 54	● Brushed stainless steel
1	8322 54	● Polished stainless steel
1	8324 54	● Gold

Pack	Cat.Nos.	Data sockets CAT. 6
		Rapid cable connection Flush mounting back box : min. 35 mm deep Nominal plate dimensions : 86 x 86 mm
		<b>RJ 45 - single</b>
1	8320 56	● Brushed stainless steel
1	8322 56	● Polished stainless steel
1	8324 56	● Gold
		<b>RJ 45 - twin</b>
1	8320 57	● Brushed stainless steel
1	8322 57	● Polished stainless steel
1	8324 57	● Gold

Pack	Cat.Nos.	Television sockets
		Flush mounting back box : min. 35 mm deep Screened Nominal plate dimensions : 86 x 86 mm
		<b>TV sockets - single male</b>
1	8320 40	● Brushed stainless steel
1	8322 40	● Polished stainless steel
1	8324 40	● Gold
		<b>SAT sockets - single "F" type</b>
1	8320 41	● Brushed stainless steel
1	8322 41	● Polished stainless steel
1	8324 41	● Gold
		<b>TV-R-SAT sockets - "F" type</b>
1	8320 43	● Brushed stainless steel
1	8322 43	● Polished stainless steel
1	8324 43	● Gold



8320 95

8322 96



8320 52

Sleek design

BSS: Plates made of austenitic Stainless Steel - non-magnetic - grade 304 L

PSS: Plates made of Stainless Steel + rust resistance

G: Plates made of Stainless Steel + rust resistance

Terminal screws captive and backed off ready for cabling - large angled terminal entries

Compact mechanism for maximum wiring space

Pack	Cat.Nos.	Blanking plates
		<b>1 gang</b>
		Nominal plate dimensions : 86 x 86 mm
1	8320 95	● Brushed stainless steel
1	8322 95	● Polished stainless steel
1	8324 95	● Gold
		<b>2 gang</b>
		Nominal plate dimensions : 86 x 146 mm
1	8320 96	● Brushed stainless steel
1	8322 96	● Polished stainless steel
1	8324 96	● Gold
		<b>Cord outlets</b>
		<b>1 gang</b>
		Nominal plate dimensions : 86 x 86 mm
1	8320 52	● Brushed stainless steel
1	8322 52	● Polished stainless steel
1	8324 52	● Gold
		<b>Accessories</b>
		<b>Side extension frames</b>
		3 mm thick frames to be used when extra wiring space is needed
10	7341 98	1 gang frame
10	7341 99	2 gang frame

Download the full file at

<http://assets.kempstoncontrols.com/doc/Synergy%20Wiring%20Accessories.pdf>



**KEMPSTON**  
CONTROLS