Product data sheet Characteristics

33669

MN undervoltage release, Compact NS 630b to Compact NS 3200, 48 VDC to 60 VDC, 48 VAC 50/60 Hz



| - 1 | ١л | п | n |
|-----|----|---|---|
| | | | |

| Wichin | | 5 |
|------------------------------|---|--|
| Device short name | MN | Ö |
| Product or component type | Voltage release | |
| Device application | Control | |
| Range compatibility | Masterpact NW Compact NS1600b3200 Compact NS630b1600 Masterpact NT | as and interest of the state of |
| Offer type | C5 C4 |) |
| Voltage release type | Undervoltage release | |
| [Uc] control circuit voltage | 48 V AC 4860 V DC | isbiility |
| | | |

Complementary

| The section of the Control of the co | 0.05 0.711. d. day a said a fina | |
|--|----------------------------------|--------------|
| Threshold tripping voltage | 0.350.7 Un - during opening time | - |
| | 0.85 Un - during closing time | , |
| Supply holding power | 4.5 W | 9 |
| Mounting mode | Fixed | <u> </u> |
| Response time | 40 ms Masterpact NT | |
| · | 90 ms Masterpact NW | ž. 2 |
| Accessory / separate part category | Spare parts Masterpact NT | Ş |
| | Spare parts Masterpact NW | 9 |
| | Spare parts Compact NS1600b3200 | |
| | Spare parts Compact NS630b1600 | ū |
| | | |

Contractual warranty

| on the details in an array | | |
|----------------------------|-----------|--|
| Warranty period | 18 months | |