



BOURDON
The Original by Baumer

EN-837-3

IP 33/44

Main Features

- Low pressure measurements
- Class 1.6 according to EN 837-3
- Wetted parts Stainless steel (MTX5) or Brass (MTA5)
- For non corrosive (MTA5) and corrosive gases (MTX5)


Applications

- Laboratory & Medical
- Machinery


Technical Data

Nominal size	100 mm
Measurement ranges	0 ... 16 to 0 ... 600 mbar and corresponding vacuum and compound pressure ranges
Pressure limitation	Steady : 75% of full scale value Fluctuating : 65% of full scale value Short time : 100% of full scale value
Accuracy	Class 1.6 (according EN837-3)
Protection rating (EN 60529)	IP 44 (Type B-F-E) IP 33 (Type A-D)
Process Connection	MTA5 : Brass MTX5 : Stainless steel
Capsule	Stainless steel 1.4404 (AISI 316L)
Case	Stainless steel 1.4301 (AISI 304)
Movement	Brass
Front flange	ABS, black (for type B)
Window	Polycarbonate, snap-fitted into the case
Dial	Aluminium, white
Pointer	Aluminium, black
Temperature	Ambient: -20...60°C Medium: -20...60°C Storage: -40...70°C
Thermal drift	± 0.4 % F.S. / 10 K (reference 20°C)
Zero adjustment	± 10 % of full scale value Adjustment screw accessible on the front side after removing of the window



Dimensions - Types of mounting




Type D




Type A




Type F



Type E



Type B



mm	A	B	C	D	E	F	G	H	I	J	K	L	M	S
NS 100	99	66	132	34.5	130	33.5	40.5	49.5	53.5	52.5	8.5	101	51	23

Weight
0.350 kg

Pressure ranges

Code	Ranges mbar
N50	-16 ... 0 ¹⁾
N51	-25 ... 0
N52	-40 ... 0
N53	-60 ... 0
N54	-100 ... 0
N55	-160 ... 0
N56	-250 ... 0
N57	-400 ... 0
N58	-600 ... 0

Code	Ranges mbar
N04	0 ... 16 ¹⁾
N05	0 ... 25
N06	0 ... 40
N07	0 ... 60
N08	0 ... 100
N09	0 ... 160
N10	0 ... 250
N11	0 ... 400
N12	0 ... 600

Code	Ranges mbar
N61	-6 ... 10 ¹⁾
N62	-10 ... 16
N63	-16 ... 25
N64	-25 ... 40
N65	-40 ... 60
N66	-60 ... 100
N67	-100 ... 160
N68	-160 ... 250
N69	-250 ... 400

¹⁾ Graduation 180°, accuracy class 2.5

