

BZS/F label rail - black - 9 and 15 mm



BZS/F rail (cover and label not included in the delivery)

PRODUCT INFORMATION

The BZS/F labelling system was developed as a simple means of accommodating a great deal of labelling information in or on the control cabinet.








The label holder with the snap-in labels provides vertical and horizontal designations on terminal blocks and other components. It may be fitted on the top-hat rail, C-rail or the cable duct with a high degree of flexibility.

The label holder can be cut to any length.

9 mm and 15 mm widths.

- BZS/F: with pre-punched holes (distance between holes 100 mm; hole diameter 3.6 mm).
- BZS/F K: with pre-punched holes (distance between holes 100 mm; hole diameter 3.6 mm) and adhesive strip (adhesive 4930) as a mounting aid
- BZS/F SK: self-adhesive label rail (adhesive 1780) without drilled holes for uneven surfaces (hammered enamel)

SPECIFICATIONS

	Polyvinyl chloride (PVC)
	BZS/F K with adhesive 4930 BZS/F SK with adhesive 1780
	-40 – 80 °C
	V0
	
	
	

The BZS/F label holders are available in

Type	Order No.	Colour	Length mm	Width mm	Recommended Label plate	Pack qty.
Label rail with drilled holes at 9 mm width						
BZS/F 09 - 500	86301634	Black	500.00	9.00	KSO x/9	25
BZS/F 09 - 600	86301636	Black	600.00	9.00	KSO x/9	25
BZS/F 09 - 1000	86301638	Black	1000.00	9.00	KSO x/9	25
BZS/F 09 - 1300	86301640	Black	1300.00	9.00	KSO x/9	25
Label rail with drilled holes and adhesive strips (adhesive 4930) as assembly aid at 9 mm width						
BZS/F 09 - 500 K	86301684	Black	500.00	9.00	KSO x/9	25
BZS/F 09 - 600 K	86301686	Black	600.00	9.00	KSO x/9	25
BZS/F 09 - 1000 K	86301688	Black	1000.00	9.00	KSO x/9	25
BZS/F 09 - 1300 K	86301690	Black	1300.00	9.00	KSO x/9	25
Self-adhesive label rail (adhesive 1780) without drilled holes for uneven surfaces (hammered enamel) at 9 mm width						
BZS/F 09 - 500 SK	86301654	Black	500.00	9.00	KSO x/9	25
BZS/F 09 - 600 SK	86301656	Black	600.00	9.00	KSO x/9	25
BZS/F 09 - 1000 SK	86301658	Black	1000.00	9.00	KSO x/9	25
BZS/F 09 - 1300 SK	86301660	Black	1300.00	9.00	KSO x/9	25
Label rail with drilled holes at 15 mm width						
BZS/F 15 - 500	86301834	Black	500.00	15.00	KS 15/x	25
BZS/F 15 - 600	86301836	Black	600.00	15.00	KS 15/x	25

BZS/F label rail - black - 9 and 15 mm

Type	Order No.	Colour	Length mm	Width mm	Recommended Label plate	Pack qty.
BZS/F 15 - 1000	86301838	Black	1000.00	15.00	KS 15/x	25
BZS/F 15 - 1300	86301840	Black	1300.00	15.00	KS 15/x	25
Label rail with drilled holes and adhesive strips (adhesive 4930) as assembly aid at 15 mm width						
BZS/F 15 - 430 K	86301885	Black	430.00	15.00	KS 15/x	25
BZS/F 15 - 500 K	86301884	Black	500.00	15.00	KS 15/x	25
BZS/F 15 - 600 K	86301886	Black	600.00	15.00	KS 15/x	25
BZS/F 15 - 630 K	86301887	Black	630.00	15.00	KS 15/x	25
BZS/F 15 - 650 K	86301889	Black	650.00	15.00	KS 15/x	25
BZS/F 15 - 1000 K	86301888	Black	1000.00	15.00	KS 15/x	25
BZS/F 15 - 1300 K	86301890	Black	1300.00	15.00	KS 15/x	25
Self-adhesive label rail (adhesive 1780) without drilled holes for uneven surfaces (hammered enamel) at 15 mm width						
BZS/F 15 - 430 SK	86301855	Black	430.00	15.00	KS 15/x	25
BZS/F 15 - 500 SK	86301854	Black	500.00	15.00	KS 15/x	25
BZS/F 15 - 600 SK	86301856	Black	600.00	15.00	KS 15/x	25
BZS/F 15 - 630 SK	86301857	Black	630.00	15.00	KS 15/x	25
BZS/F 15 - 650 SK	86301859	Black	650.00	15.00	KS 15/x	25
BZS/F 15 - 1000 SK	86301858	Black	1000.00	15.00	KS 15/x	25
BZS/F 15 - 1300 SK	86301860	Black	1300.00	15.00	KS 15/x	25

MATERIAL PROPERTIES



Polyvinyl chloride (PVC)

BZS/F K with adhesive 4930
BZS/F SK with adhesive 1780

THERMAL PROPERTIES

Temperature / temperature range
-40 – 80 °C

FIRE BEHAVIOUR

Fire classification
V0

INSTALLATION METHOD



Adhesive system



Riveting system



Screw assembly system

BZS/F label rail - black - 9 and 15 mm

All details given in our sales brochures and catalogues, as well as the information available online, are based on our current knowledge of the products described.

The electronic data and files made available by Murrplastik, particularly CAD files are based on our current knowledge of the product described.

A legally binding assurance of certain properties or the suitability for a certain purpose can not be determined from this information.

All information with respect to the chemical and physical properties of Murrplastik products, as well as application advice given verbally, in writing or by tests, is given to the best of our knowledge.

This does not free the purchaser of carrying out their own inspections and tests in order to determine the suitability of a product for a specific purpose.

Murrplastik accepts no responsibility for the available information being up-to-date, correct or complete. Neither do we accept responsibility for the quality of this information.

Murrplastik accepts no liability for damage caused as a result of using our products.

Murrplastik reserves the right to make technical changes and improvements through constant further development of products and services.

Our General Terms and Conditions apply.

© Murrplastik Systemtechnik GmbH • proID_60917~20180504~890286~acs_mod_bzs_sw_9_15