



TD 422-01y-1090/2512

- 2 cable entries M 20 x 1.5
- Actuator head can be repositioned in steps 4 x 90°
- Metal enclosure
- Continuous adjustment of lever position 360°
- Lever can be transposed by 180°
- 1 Contact
- 106 mm x 71 mm x 63 mm (basic component)
- In temperature-resistant version, the roller can be mounted in two different positions on the shaft
- Protection class IP65

Data

Ordering data

Product type description	TD 422-01y-1090/2512
Article number (order number)	151180784
eCl@ss number, version 12.0	27-27-06-01
eCl@ss number, version 11.0	27-27-06-01
eCl@ss number, version 9.0	27-27-06-01
ETIM number, version 7.0	EC000030
ETIM number, version 6.0	EC000030

Approvals - Standards

Certificates	CCC
--------------	-----

General data

Standards	EN IEC 60947-5-1
Working principle	mechanical

Slide form	Castor
Housing material	Grey cast iron, galvanised
Housing coating material	painted
Material resistance (acids)	good to excellent
Gross weight	1,480 g

General data - Features

Number of normally closed (NC)	1
--------------------------------	---

Safety classification - Safety outputs

B _{10D} Normally-closed contact (NC)	2,000,000 Operations
---	----------------------

Mechanical data

Actuating element	Roller lever
Roller material	Plastic
Mechanical life, minimum	10,000,000 Operations
Actuating angle, from left of switch axis	30 °
Actuating angle, from right of switch axis	30 °
Contact opening	2 x 6 mm
Actuating speed, minimum	1 mm/min
Actuating speed, maximum	3 m/s
Note (Actuating speed)	Actuating speed with vertical actuating angle to switch axis

Mechanical data - Connection technique

Termination	Screw terminals M20 x 1.5
Cable section, minimum	1.5 mm ²
Cable section, maximum	2.5 mm ²
Note (Cable section)	All indications including the conductor ferrules.
Wire cross-section	13 AWG

Mechanical data - Dimensions

Length of sensor	63 mm
Width of sensor	106 mm
Height of sensor	209 mm
Width of Castor	9 mm
Diameter of Castor	36 mm

Ambient conditions

Degree of protection	IP65
Ambient temperature	-30 ... +90 °C

Ambient conditions - Insulation values

Rated insulation voltage U_i	400 V
--------------------------------	-------

Electrical data

Thermal test current	16 A
Utilisation category AC-15	400 VAC
Utilisation category AC-15	4 A
Switching element	Opener (NC)
Note (Switching element)	with double break
Switching principle	Slow action
Material of the contacts, electrical	Silver

Ordering code

Product type description:
T(1) 422-(2)Y-(3)

(1)

S	Plunger S
2S	Telescopic plunger 2S

R	Roller plunger R
K	Offset roller lever K
J	Offset roller lever J
2C	Fork lever 2C
L	Roller lever L
D	Roller lever D
(2)	
01	1 NC contact
10	1 NO contact
(3)	
T	temperature-resistant and tropical version with ceramic insulation for -40 °C ... +200 °C
1276-2	Gold-plated contacts
2186	Protection class IP66
1090	Swivel lever attachment made of seawater-resistant brass Rated voltage 500 VAC

Pictures

Product picture (catalogue individual photo)




ID: kt422f09

| 469.4 kB | .jpg | 209.55 x 375.708 mm - 594 x 1065 px - 72 dpi

| 72.9 kB | .png | 74.083 x 132.644 mm - 210 x 376 px - 72 dpi

| 45.5 kB | .jpg | 68.792 x 123.472 mm - 195 x 350 px - 72 dpi

Dimensional drawing basic component




ID: 1t422g01

| 29.4 kB | .cdr |

| 3.6 kB | .png | 74.083 x 51.858 mm - 210 x 147 px - 72 dpi

| 82.3 kB | .jpg | 352.778 x 247.297 mm - 1000 x 701 px - 72 dpi

Dimensional drawing actuator



ID: 1t422b08

| 10.2 kB | .png | 74.083 x 51.153 mm - 210 x 145 px - 72 dpi

| 121.4 kB | .jpg | 352.778 x 243.769 mm - 1000 x 691 px - 72 dpi

Switch travel diagram



ID: kt422s07

| 43.6 kB | .ai | 297 x 210.002 mm - 841 x 595 px - 72 dpi

| 937.0 b | .png | 74.083 x 52.564 mm - 210 x 149 px - 72 dpi

| 35.1 kB | .jpg | 352.778 x 84.314 mm - 1000 x 239 px - 72 dpi

Operating principle



ID: 235hz05

| 15.2 kB | .cdr |

| 180.5 kB | .jpg | 352.778 x 749.3 mm - 1000 x 2124 px - 72 dpi

| 3.4 kB | .png | 74.083 x 157.339 mm - 210 x 446 px - 72 dpi

Schmersal Ltd., Sparrowhawk Close, WR14 1GL Malvern

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 20/02/2024, 10:37