



## NEMA/EEMAC Terminal Blocks

### Fuse Blocks

	1492-H4			1492-H5			1492-H6		
Dimensions are not intended to be used for manufacturing purposes. <b>Note:</b> Height dimension is measured from top of rail to top of terminal block.									
<b>Specifications</b>	<i>Single-circuit fusible terminal block with neon blown fuse indicator.</i>			<i>Single-circuit fusible terminal block with LED blown fuse indicator.</i>			<i>Single-circuit fusible terminal block without a blown fuse indicator.</i>		
Approvals		CSA	IEC		CSA	IEC		CSA	IEC
Voltage Rating	300V AC/DC	300V AC/DC	500V AC/DC	300V AC/DC	300V AC/DC	500V AC/DC	300V AC/DC	300V AC/DC	500V AC/DC
Maximum Current	15 A	12 A	12 A	12 A	12 A	12 A	15 A	15 A	12 A
Wire Range (Rated Cross Section)	#30...#12 AWG	#30...#12 AWG	0.05...4 mm <sup>2</sup>	#30...#12 AWG	#30...#12 AWG	0.05...4 mm <sup>2</sup>	#30...#12 AWG	#30...#12 AWG	0.05...4 mm <sup>2</sup>
Indicator Type	Neon			LED			Non-Indicating		
Leakage Current	2 mA @ 300V			2 mA @ 24V			—		
Working Voltage	100...300V AC			10...57V AC/DC			Per Fuse Rating		
Fuse Size (Not Supplied)	1/4 in. x 1-1/4 in.			1/4 in. x 1-1/4 in.			1/4 in. x 1-1/4 in.		
Wire Strip Length	0.38 in. (9.7 mm)			0.38 in. (9.7 mm)			0.38 in. (9.7 mm)		
Recommended Tightening Torque	3...7 lb-in. (0.3...0.8 N•m)			3...7 lb-in. (0.3...0.8 N•m)			3...7 lb-in. (0.3...0.8 N•m)		
Density	33 pcs./ft (109/m)			33 pcs./ft (109/m)			33 pcs./ft (109/m)		
Insulation Temperature Range	-40...+221 °F (-40...+105 °C)			-40...+221 °F (-40...+105 °C)			-40...+221 °F (-40...+105 °C)		
<b>Terminal Blocks</b>	<b>Cat. No.</b>	<b>Pcs./Pkg.</b>		<b>Cat. No.</b>	<b>Pcs./Pkg.</b>		<b>Cat. No.</b>	<b>Pcs./Pkg.</b>	
Black with Neon	1492-H4	25		1492-H5	25		1492-H6	25	
<b>Accessories (Accessories)</b>	<b>Cat. No.</b>	<b>Pcs./Pkg.</b>		<b>Cat. No.</b>	<b>Pcs./Pkg.</b>		<b>Cat. No.</b>	<b>Pcs./Pkg.</b>	
Mounting Rails:									
A-B Rail	1492-N1	20		1492-N1	20		1492-N1	20	
3 ft Rigid A-B Rail	1492-N22	20		1492-N22	20		1492-N22	20	
3 ft High-Rise A-B Rail	1492-N44	2		1492-N44	2		1492-N44	2	
Standoff Brackets (use every 12 in.)	1492-N25	2		1492-N25	2		1492-N25	2	
1 m Symmetrical DIN	199-DR1	10		199-DR1	10		199-DR1	10	
1 m Symmetrical DIN (Aluminum)	1492-DR5	10		1492-DR5	10		1492-DR5	10	
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR6	2		1492-DR6	2		1492-DR6	2	
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7	2		1492-DR7	2		1492-DR7	2	
End Barrier	1492-N37	50		1492-N37	50		1492-N37	50	
End Anchors:									
A-B Rail	1492-N23	10		1492-N23	10		1492-N23	10	
A-B Rail — Normal Duty	1492-N47	50		1492-N47	50		1492-N47	50	
DIN Rail — Normal Duty	1492-EA35	50		1492-EA35	50		1492-EA35	50	
DIN Rail — Heavy Duty	1492-EAH35	10		1492-EAH35	10		1492-EAH35	10	
Side Jumpers:									
Side Jumper — 10-pole Uninsulated	1492-N49	10		1492-N49	10		1492-N49	10	
Side Jumper Insulating Sleeve	1492-SJS	10		1492-SJS	10		1492-SJS	10	
Marking Systems	1492-MS8X12 (56/sheet)	5		1492-MS8X12 (56/sheet)	5		1492-MS8X12 (56/sheet)	5	

	1492-CE6		1492-UF3	
Dimensions are not intended to be used for manufacturing purposes. <b>Note:</b> Height dimension is measured from top of rail to top of terminal block.				
<b>Specifications</b>	<b>13/32" x 1-1/2" fuse block with screw terminals and wire clamp.</b>		<b>GMT-style fuse block with blown fuse alarm circuit, finger-safe.</b>	
Approvals	<b>UL/CSA</b>		<b>UL/CE</b>	
Voltage Rating	600V AC/DC		125V AC, 60V DC	
Maximum Current	10 A		4 A	
Wire Range (Rated Cross Section)	#22...#10 AWG (0.5...6 mm <sup>2</sup> )		#30...#12 AWG (0.05...4 mm <sup>2</sup> )	
Wire Strip Length	0.38 in. (9.7 mm)		0.38 in. (9.7 mm)	
Recommended Tightening Torque	10...16 lb-in. (1.1...1.8 N•m)		3...7 lb-in. (0.3...0.8 N•m)	
Fuse Size (Not Supplied)	13/32 in. x 1-1/2 in. Fuse		Bussmann GMT-Type Alarm Fuse	
Leakage Current (Indicator Circuit)	—		—	
Density	16 pcs./ft (52/m)		40 pcs./ft (131/m)	
Insulation Temperature Range	-40...+221 °F (-40...+105 °C)		-40...+221 °F (-40...+105 °C)	
<b>Terminal Blocks</b>	<b>Cat. No.</b>	<b>Pcs./ Pkg.</b>	<b>Cat. No.</b>	<b>Pcs./ Pkg.</b>
Terminal Block	1492-CE6	10	1492-UF3	40
Terminal Block: Two 3' Rails White	1492-CE695	1	—	—
<b>Accessories (Accessories)</b>	<b>Cat. No.</b>	<b>Pcs./ Pkg.</b>	<b>Cat. No.</b>	<b>Pcs./ Pkg.</b>
Mounting Rails:				
A-B Rail	1492-N1	20	1492-N1	20
3 ft Rigid A-B Rail	1492-N22	20	1492-N22	20
3 ft High-Rise A-B Rail	1492-N44	2	1492-N44	2
Standoff Brackets (use every 12 in.)	1492-N25	2	1492-N25	2
1 m Symmetrical DIN	—	—	199-DR1	10
1 m Symmetrical DIN (Aluminum)	—	—	1492-DR5	10
1 m Hi-Rise Sym. DIN (Aluminum)	—	—	1492-DR6	2
1 m Angled Hi-Rise Sym. DIN (Steel)	—	—	1492-DR7	2
End Barrier	1492-N17	50	Not Required	—
End Anchors:				
A-B Rail	1492-N23	10	1492-N23	10
A-B Rail — Normal Duty	1492-N47	50	1492-N47	50
DIN Rail — Normal Duty	—	—	1492-EA35	50
DIN Rail — Heavy Duty	—	—	1492-EAH35	10
Side Jumpers:				
Side Jumper — 10-pole Uninsulated	—	—	1492-N46	10
Fuse Puller	1492-N12	50	—	—
Marking Systems	—	—	1492-MN81	5