

# DS202C M C32 A30 110V



DS202C M C32 A30 110V - RCBO

## General Information

|                       |   |
|-----------------------|---|
| Extended Product Type | DS202C M C32 A30 110V   |
| Product ID            | 2CSR272199R1324   |
| EAN                   | 8012542079439   |
| Catalog Description   | DS202C M C32 A30 110V - RCBO  |
| Long Description      | The DS202C series RCBO is a 2P in two-modules device for the protection of end user single-phase circuits against overload and short-circuit currents |

## Ordering

|                        |          |
|------------------------|----------|
| Minimum Order Quantity | 1 piece  |
| Customs Tariff Number  | 85363030 |

## Popular Downloads

|                                   |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 2CSC400002D0209 |
| Instructions and Manuals          | 9AKK106354A0766 |

## Dimensions

|                            |          |
|----------------------------|----------|
| Product Net Width          | 0.035 m  |
| Product Net Height         | 0.085 m  |
| Product Net Depth / Length | 0.069 m  |
| Product Net Weight         | 0.239 kg |

## Technical

|   |                              |
|---|------------------------------|
| Standards                                 | IEC 61009-1<br>IEC 61009-2-1 |
| Type of Residual Current                  | A type                       |
| Rated Residual Current                    | 30 mA                        |
| Tripping Characteristic                   | C                            |
| Rated Current ( $I_n$ )                   | 32 A                         |
| Number of Poles                           | 2                            |
| Number of Protected Poles                 | 2                            |
| Rated Short-Circuit Capacity ( $I_{cn}$ ) | (230 / 400 V AC) 10 kA       |
| Position of Neutral Terminals             | Right                        |

|                                 |              |
|---------------------------------|--------------|
| Power Loss                      | 8.2 W        |
| Rated Voltage (U <sub>r</sub> ) | 230-240 V AC |

---

## Environmental

|                         |  |
|-------------------------|--|
| Ambient Air Temperature | Operation -25 ... +55 °C<br>Storage -40 ... +70 °C |
| RoHS Status             | Following EU Directive 2011/65/EU                  |

---

## Certificates and Declarations (Document Number)

|                                |                          |
|--------------------------------|--------------------------|
| Declaration of Conformity - CE | 9AKK106713A5589          |
| Environmental Information      | refer to RoHS infmration |
| Instructions and Manuals       | 9AKK106354A0766          |
| RoHS Information               | 2CSC422002K2701          |

---

## Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Units          | 5 piece       |
| Package Level 1 Width          | 0.253 m       |
| Package Level 1 Height         | 0.108 m       |
| Package Level 1 Depth / Length | 0.088 m       |
| Package Level 1 Gross Weight   | 1.446 kg      |
| Package Level 1 EAN            | 8012542079446 |

---

## Classifications

|                            |  |
|----------------------------|--|
| Object Classification Code | Q  |
| ETIM 4                     | EC000905 - Earth leakage circuit breaker |
| ETIM 5                     | EC000905 - Earth leakage circuit breaker |
| ETIM 6                     | EC000905 - Earth leakage circuit breaker |
| ETIM 7                     | EC000905 - Earth leakage circuit breaker |

---

## Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Residual Current Devices RCDs → Residual Current Circuit Breakers with Overcurrent Protection RCBO

