

## Datasheet

Art.No. 91.932.3053.0

Male connector with strain relief GST15I3S S1 ZR1W WS

Connector GST15i3, 3 pole, male, screw connection, 250V/16A, color of coding: white, color of housing: white



Art.No.	91.932.3053.0
EAN	4015573833838
Order unit	1 pieces

## Approvals



## Technical data

### General

Rated current	16 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Strain relief	Yes
Pollution degree	2
Mechanical coding	Code 1
Lockable	Yes
Color of coding/ contact carrier	White
Marking of poles	L, N, PE
Color of housing inclusive strain relief	White

### Connection Data

Cable diameter	9 mm
Cable diameter 2	5.5 mm
Cross section solid	2.5 mm <sup>2</sup>
Cross section solid 2	0.5 mm <sup>2</sup>
Connection cross section stranded (max.)	2.5 mm <sup>2</sup>
Cross section stranded 2	0.5 mm <sup>2</sup>
Terminations per pole	1
sheath strip length	25 mm
Wire strip length	8 mm

**Model**

Model	male
Connection type	Screw connection
Degree of protection (IP)	IP20

**Material**

Housing material	Polyamide
Halogen free	Yes
Contact material	CuZn
Insulation components continuous temperature	100 °C
Surface finish	Silver-plated

**Dimensions**

Length	53.2 mm
Width	23 mm
Height	13.8 mm

**Classification**

ECLASS 8.1	27440605
ETIM 6.0	EC002560
ETIM 5.0	EC002560
ETIM 4.0	EC002560