



Main

| | |
|---------------------------|--|
| Range | Acti 9 |
| Product name | Acti 9 Isobar P B |
| Product or component type | Distribution board |
| Device application | Distribution |
| Enclosure type | Standard |
| Provided equipment | Door Enclosure Earth terminal block Neutral terminal block Earth stud Removable gland plates Blanking plate Front cover Pan assembly |
| Colour | Cream RAL 9001 |

Complementary

| | |
|--|--|
| Enclosure mounting | Surface |
| Poles description | 3P + N |
| [Ie] rated operational current | 250 A 400/415 V AC 250 A 230/240 V AC |
| Breaking capacity | 25 kA |
| Overvoltage category | IV |
| [Ui] rated insulation voltage | 500 V |
| [Uimp] rated impulse withstand voltage | 6 kV |
| Incomer device options | Switch disconnecter 3P + N Switch disconnecter 4P MCCB 4P Terminal block 4P Contactor 4P RCCB 4P |
| Protection device options at outgoing | Miniature circuit breaker (MCB) 63 A max Residual current circuit breaker with overcurrent protection (RCBO) 45 A max 100 mA max Residual current circuit breaker with overcurrent protection (RCBO PoN) 45 A max 100 mA max |
| Number of ways | 12 ways as outgoing - 3P |
| Enclosure material | Steel |

| | |
|-------------------|--------------|
| Surface treatment | Epoxy |
| Surface finish | Powder paint |
| Height | 700 mm |
| Width | 470 mm |
| Depth | 139 mm |
| Product weight | 13.5 kg |

Environment

| | |
|---------------------------------------|---|
| Standards | BS EN 61439-3 |
| IP degree of protection | IP2x without cover internal BS EN 60529 IP3x with cover external BS EN 60529 |
| IK degree of protection | IK05 |
| Ambient air temperature for operation | -35...70 °C |
| Ambient air temperature for storage | -40...80 °C |

Offer Sustainability

| | |
|----------------------------------|---------------------------------------|
| Product environmental profile | Available |
| Product end of life instructions | Need no specific recycling operations |