

Datasheet - NDTP30GR/SW

Command and signalling devices / Push buttons and pilot lights - "N" Program / NDTP -
Mushroom button



(Minor differences between the printed image and the original product may exist!)

Ordering details

Product type description	NDTP30GR/SW
Article number	103009111
EAN code	
eCl@ss	27-37-12-12

Approval

Approval



BG

Global Properties

Product name	Schlagtaster NDTP
Standards	IEC/EN 60947-1, EN 60947-5-1
Compliance with the Directives (Y/N)	No
Suitable for safety functions (Y/N)	No
Mounting	mounting flange EFM
Materials	
- Material of the operators	Plastic
- Material of the front ring	ABS, Chromium-plated
- Material of the bellows	Silicone
Design	Round
Form	Round
Color	
- Colour of the operating element	■ Black
- Colour of the bellows	■ Black
- Colour of the front ring	■ Silver
Weight	36 g
Can be illuminated (Y/N)	No
Manner of using	Mushroom button

Mechanical data

Actuating stroke	5 mm
------------------	------

Latching (Y/N)	No
Probing possible (Y/N)	Yes
Front plate thickness	
- min. front plate thickness	1.5 mm
- max. front plate thickness	6 mm
Tightening torque for fixing screws	0,6 Nm
mounting flange available (Y/N)	Yes

Ambient conditions

Ambient temperature	
- Min. environmental temperature	-25 °C
- Max. environmental temperature	+80 °C
Storage and transport temperature	
- Min. Storage and transport temperature	-
- Max. Storage and transport temperature	-
Fully insulated (Y/N)	Yes
Sealing type	membrane, lip seal
Protection type IP	IP67, IP69K

Dimensions

Dimensions	
- Height	20 mm
- diameters for the actuating heads	Ø 30 mm
- Hole, diameter	22.3 mm + 0,4 mm
Spacing	50 x 50 mm

Documents

Operating instructions and Declaration of conformity (it) 2 MB, 14.06.2017

Code: mrl_programme-e-n-r_it

Operating instructions and Declaration of conformity (en) 2 MB, 17.05.2017

Code: mrl_programme-e-n-r_en

Operating instructions and Declaration of conformity (pl) 2 MB, 31.10.2016

Code: mrl_programme-e-n-r_pl

Operating instructions and Declaration of conformity (jp) 2 MB, 28.06.2017

Code: mrl_programme-e-n-r_jp

Operating instructions and Declaration of conformity (pt) 2 MB, 31.05.2017

Code: mrl_programme-e-n-r_pt

Operating instructions and Declaration of conformity (de) 2 MB, 17.05.2017

Code: mrl_programme-e-n-r_de

Operating instructions and Declaration of conformity (es) 2 MB, 01.06.2017

Code: mrl_programme-e-n-r_es

Operating instructions and Declaration of conformity (fr) 2 MB, 22.05.2017

Code: mrl_programme-e-n-r_fr

Operating instructions and Declaration of conformity (cn) 2 MB, 21.06.2017

Code: mrl_programme-e-n-r_cn

BG-test certificate (de, en, fr) 174 kB, 31.07.2014

Code: z_ndrp01

IPA Data (en) 248 kB, 09.11.2012

Code: i_ipap02

IPA Data (de) 255 kB, 05.09.2014

Code: i_ipap01

System components

Accessories



101014388 - EFM

contact element



contact element EF

- Screw connection
- Mounting flange position 1
- 23-24; 11-12 (Contact labelling)

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, D-42279 Wuppertal

The data and values have been checked thoroughly. Technical modifications and errors excepted.

Generiert am 17.08.2017 - 10:48:15h Kasbase 3.2.7.F.64l