



# KEMPSTON CONTROLS

**Honeywell**

Availability	Global
Operating Force (OF)	6,95 N to 11,12 N [25 oz to 40 oz]
Release Force	2,78 N [10 oz] min.
Pretravel (PT)	0,38 mm [0.015 in] max.
Overtravel (OT)	3,55 mm [0.140 in] min.
Differential Travel (DT)	0,05 mm [0.002 in] max.
Product Type	Enclosed Switches
Actuator	Top Roller Plunger
Circuitry	1NC 1NO SPDT Snap Action
Ampere Rating	5 A Ind./0.5 A Res./0.25 A Res.
Supply Voltage	125 Vac, 250 Vac, 480 Vac/125 Vdc/250 Vdc
Housing Material	Zinc Die-Cast
Termination Type	0.5 in - 14NPT Conduit
Housing Type	Split Housing, Side Mount
Series Name	E6/V6
Sealing	IP40; NEMA 1
UL File #	E12252
Operating Temperature	-32 °C to 71 °C [-25 °F to 160 °F]
Comment	Without seal boot on plunger; High Operating Force
Agency Approvals and Standards	UL, CSA
UNSPSC Code	302119
UNSPSC Commodity	302119 Switches and controls and relays
Sealed	Industrial