




B A R G

> 100 dB <
> 16 TONES <
> 3 LEVELS OF ALARM <



CH 1/2

CAN BE INSTALLED WITH

G B R W

See Base Section on page 30

	SHALLOW	DEEP	WALL
12/24V ACDC	✓	✓	✓
PNP 12/24V DC	✗	✗	✓
40/80V ACDC	✗	✓	✓
120/240V AC	✗	✓	✓
JR 120/240V AC	✗	✗	✓
	FLUSH	DOUBLE	POLE

SIR-E LED JUNIOR | PART NO

	B	A	R	G
EURO	90401	90402	90403	90404
APAC	90421	90422	90423	90424

SIR-E LED JUNIOR

Multifunctional LED beacon sounder developed with a multilevel technology that allows three separate levels of alarm (alert, pre-alarm, alarm) controllable via independent electric contacts. SIR-E LED JUNIOR benefits from two light effects (steady, flashing) and 16 different tones (selectable via dip-switch).

European (EURO) and Asia Pacific (APAC) tones available.

TECHNICAL SPECIFICATIONS

MULTIFUNCTION

3 levels of alarm (alert, pre-alarm, alarm) controllable via independent electric contacts

HIGH OPTICAL AND ACOUSTIC PERFORMANCE

CHANNEL 1 | ALERT

A triple-flash strobe effect that guarantees catching attention and warns operators of a potential danger or change of operating circumstances

CHANNEL 2 | PRE-ALARM

A triple-flash strobe effect combined with an up to 100 dB electronic tone, ideal for alerting staff of a danger or a serious change of operating circumstances (tone selectable via dip switch "A" out of 8 tones)

CHANNEL 3 | ALARM

A powerful steady light combined with an up to 100 dB electronic tone, ideal for alerting staff of a permanent change of operating circumstances (tone selectable via dip switch "B" out of 8 tones)

MULTITONE

16 tones available, including fire alarm, industrial and civil tones

VOLTAGES

According to the installed base

PROTECTION GRADE

IP65, UL TYPE 3R, suitable for outdoor applications

OPERATING TEMPERATURE

-30/+50 °C

LED TECHNOLOGY

Virtually zero maintenance thanks to the built-in LED technology that guarantees up to 100.000* hours of product life

* At normal conditions, without vibrations and heavy temperature changes

MECHANICAL FEATURES

Self extinguishing PC body with high impact resistance, suitable for outdoor applications thanks to the IP65/TYPER 3R protection grade

OPTICAL FEATURES

4 x Bright LEDs over 360°

CERTIFICATIONS



DRAWINGS, DIMENSIONS AND WEIGHTS

