Product datasheet
Characteristics

A9A27108
ACTI9 IMN 24VAC / 24VDC Undervoltage release

Main

Range	Acti 9
Range of product	IDPN Vigi IC60 ISW-NA IID
Product or component type	Undervoltage release
Device short name	IMN
Device application	Protection
[Uc] control circuit voltage	24 V AC 50/60 Hz 24 V DC
Control type	Toggle
9 mm pitches	2
Product compatibility	IID IDPN Vigi ISW-NA IC60 Double terminal Single terminal

Complementary

Protection type	Undervoltage
Range compatibility	Acti 9: Acti 9 iDPN Vigi Acti 9: Acti 9 iID Acti 9: Acti 9 iSW-NA Acti 9: Acti 9 iC60 (double terminals miniature circuit breaker)
Local signalling	Red indicator light on the front face
Mounting mode	Clip-on
Mounting support	DIN rail
Height	85 mm
Width	17.5 mm
Depth	73 mm
Product weight	69 g
Colour	White
Connections - terminals	Clamp terminal bottom 1 cable(s) 1...6 mm² rigid without cable end cable end Clamp terminal bottom 1 cable(s) 0.5...4 mm² flexible without cable end cable end Clamp terminal bottom 2 cable(s) 1...2.5 mm² rigid with cable end cable end

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

	Clamp terminal bottom 2 cable(s) 1...2.5 mm² rigid without cable end cable end
Wire stripping length	10 mm bottom
Tightening torque	1 N.m bottom

Environment

Standards	EN/IEC 60947-5-1
Ambient air temperature for operation	-35...70 °C
Ambient air temperature for storage	-40...85 °C

Life Is On Schneider Electric