






FBC nVent ERIFLEX Flexibar/Cable to Busbar Clamp – FBC5X4 (553405)



- Very compact clamp for connecting cable conductors or nVent ERIFLEX Flexibar to busbar without drilling
- Conductor is clamped with a pressure plate
- Clamps can be mounted and slid into position on busbar prior to connecting conductors
- Connections can be added after busbar has been mounted
- Single screw locks clamp and makes connection
- EAC compliant
- RoHS compliant



Part Number	FBC5X4
Article Number	553405
Material	Steel
Finish	Electrogalvanized
Busbar Thickness	5 mm
Complies With	IEC® 60999
Conductor Size	1 mm ² Stranded - 4 mm ² Stranded
Depth (D)	11 mm
Height (H)	23 mm
Width (W)	29 mm
Torque (TQ)	2 N-m
Unit Weight	0.016 kg
Certifications	RoHS
Standard Packaging Quantity	15 pc
UPC	78285667990
EAN-13	3479775534053

Conductor must be stripped at least a distance equal to the width of the clamp.

IEC is a registered trademark of the International Electrotechnical Commission.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2021 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.