



## Main

Range of product	Pressure
Product or component type	Pressure transmitter
Measurement type	Differential

## Complementary

Turndown	400:1
Mounting type	Direct to process Low profile Biplanar
Response time	125 ms
Measurement accuracy	+/- 0.05 % of reading
Maximum pressure	3000 psi 207 bar
Drift	+/- 0.03 % of measuring range per year, for 10 years
Communication protocol	FOUNDATION fieldbus HART

## Environment

IP degree of protection	IP67
NEMA degree of protection	NEMA 4X
Product certifications	FM CSA ATEX IEC-Ex EAC INMETRO TÜV Rheinland (SIL3) KOSHA
Standards	NACE MR01-75 NACE MR01-03

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

Warranty	5 years
----------	---------