

# Rittal – The System.

Faster – better – everywhere.

## Courtesy light – SZ 4139.190

Date : Jul 3, 2019

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# Courtesy light – SZ 4139.190

created: 03.07.2019 build on [www.rittal.com/uk-en](http://www.rittal.com/uk-en)



## Product description

|                         |   |
|-------------------------|---|
| <b>Supply includes:</b> | Courtesy light<br>Light<br>Light cover<br>Assembly parts<br>Integral door-operated switch |
|-------------------------|---|

## Product features

|                                  |  |
|----------------------------------|--|
| <b>Dimensions:</b>               | Width: 682 mm<br>Height: 117 mm<br>Depth: 50 mm  |
| <b>Rated operating voltage:</b>  | 100 V - 240 V, 1~, 50 Hz/60 Hz   |
| <b>Installation options:</b>     | TS horizontal section of the roof frame: direct<br>TS, SE vertical section: with TS adaptor bracket<br>SE sections at the front and rear of the roof frame: with TS adaptor bracket<br>SE extrusions at the side of the roof frame: direct |
| <b>Operating temperature:</b>    | Operation (environment): -15 °C...+45 °C<br>Bearing: -20 °C...+70 °C   |
| <b>Power consumption:</b>        | 18 W   |
| <b>Equipment (electrical):</b>   | Ballast: Wide-range electronic ballast<br>Light: Fluorescent lamp, base G13<br>Jack/socket (type): D, earthing-pin (type F, CEE 7/4)<br>Integral door-operated switch: yes<br>Switch (type): Integral, on/off/door-operated switch mode    |
| <b>Rated insulation voltage:</b> | 500 V DC/1s  |

|   |   |
|---|---|
| <b>Rated impulse withstand voltage, phase to earth:</b> | 1000 V AC   |
| <b>Rated impulse withstand voltage, phase to phase:</b> | 500 V AC  |
| <b>Protection category:</b>                             | I (PE conductor)  |
| <b>Connection options:</b>                              | Power supply via connectors<br>Through-wiring (creating rows of lights)   |
| <b>Light – installation type:</b>                       | Screw-fastening   |
| <b>Light cover:</b>                                     | yes   |
| <b>Packs of:</b>  | 1 pc(s).  |
| <b>Weight/pack:</b>                                     | 2.52 kg   |
| <b>Copper weight (kg per piece):</b>                    | 0   |
| <b>EAN:</b>   | 4028177320758   |
| <b>Customs tariff number:</b>                           | 94054095  |
| <b>ETIM 6.0:</b>  | EC000321  |
| <b>ETIM 5.0:</b>  | EC000321  |
| <b>eCl@ss 8.0/8.1:</b>                                  | 27189241  |
| <b>eCl@ss 7.0/7.1:</b>                                  | 27189241  |
| <b>eCl@ss 6.0/6.1:</b>                                  | 27189241  |
| <b>eCl@ss 5.1/5.1.4:</b>                                | 27189241  |
| <b>Product description:</b>                             | SZ Courtesy light, WHD: 682x117x50 mm, 18 W, 100-240 V, 50/60 Hz, with door-operated switch, with earthing-pin socket |
| <b>Approvals</b>  |   |
| <b>Certificates:</b>                                    | EAC   |
| <b>Declarations:</b>                                    | Declaration of conformity   |