

S401M-UCC20



S401M-UCC20 Miniature Circuit Breaker

General Information

Extended Product Type	S401M-UCC20
Product ID	2CCS571001R1204
EAN	7612270109852
Catalog Description	S401M-UCC20 Miniature Circuit Breaker
Long Description	MCB ,1P,UCC,20A,10kA,SMISLINE

Ordering

EAN	7612270109852
Minimum Order Quantity	1 piece
Customs Tariff Number	85363020

Dimensions

Product Net Width	18 mm
Product Net Height	91 mm
Product Net Length	75 mm
Product Net Depth / Length	75 mm
Product Net Weight	145 g

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	100 mm
Package Level 1 Height	91 mm
Package Level 1 Depth / Length	185 mm
Package Level 1 Gross Weight	145 g
Package Level 1 EAN	7612270109852

Environmental

RoHS Status	Following EU Directive 2002/95/EC August 18, 2005 and amendment
-------------	---

Additional Information

Frequency (f)	50 ... 60 Hz
Number of Poles	1
Number of Protected Poles	1
Power Loss	2.68 W
Product Main Type	S400
Product Name	Miniature Circuit Breaker
Rated Current (I_n)	20 A
Rated Voltage (U_r)	220 V DC
Rated Operational Voltage	110 V DC 220 V DC 240 V AC
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu})	(220 V DC) 10 kA
RoHS Date	20170426
Standards	IEC/EN 60947-2
Tripping Characteristic	UC-C

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	2CCC451059C0203-REV-B
Declaration of Conformity - CE	2CCC451034D0201
Environmental Information	2CCY000200D0213
Instructions and Manuals	2CCC451019M0111
RoHS Information	2CCC413008D0206
Dimension Diagram	2CCC451028C0202

Classifications

ETIM 4	EC000042 - Miniature circuit breaker (MCB)
ETIM 5	EC000042 - Miniature circuit breaker (MCB)
ETIM 6	EC000042 - Miniature circuit breaker (MCB)
ETIM 7	EC000042 - Miniature circuit breaker (MCB)
Object Classification Code	FC
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Plug-in Distribution Systems

