



Price* : 385.10 GBP



Main

Range	Thalassa
Product name	Thalassa PLA
Device application	Multi-purpose
Product or component type	Suitable enclosure
Device short name	PLA
Enclosure nominal height	1000 mm
Enclosure nominal width	500 mm
Enclosure nominal depth	320 mm
Enclosure mounting	Floor-standing
Device composition	1 top part 1 bottom part

Complementary

Body type	Sealed top and bottom part assembled with side parts
Door type	Plain front
Number of doors	1
Door opening side	Reversible 120 °
Lock type	4 points lock, 5 mm double-bar
Accessibility for operation	Rear Front
Removable parts	Door by hinges Rear panel by fixing element
Material	Polyester reinforced with fibreglass
Colour	Grey RAL 7035
Standards	UL 508 A IEC 62208
NEMA degree of protection	NEMA 3S NEMA 5

NEMA 3X
NEMA 4/4X
NEMA 12
NEMA 2
NEMA 3R
NEMA 1
NEMA 3
NEMA 13

Product certifications	Veritas UL/CUL listed DNV Marine
------------------------	--

Environment

IP degree of protection	IP65 completely sealed IEC 60529
IK degree of protection	IK10 plain door IEC 62262
Fire resistance	960 °C IEC 62208
Ambient air temperature for storage	-35...90 °C

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1511 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations
