



Representative Image

Ref. No. 110753 | Cat. No. CL45A300M2

Description: CL45A300M2 Contactor 3-pole 42V 50-60Hz AC

EAN 8425095107533

Products > Power devices > Contactors > 4. Series CL: Contactor for general purpose application 9-105A AC3

Series CL & RL, Three-pole contactor, Terminal: screw, Control Voltage (V): 42V 50-60Hz AC Max.oper.current AC1 (A):60Max.oper.current AC3 (A):40 Admissible power 220V/230V (kW):11 Admissible power 380V/400V (kW):18.5

Descriptors

Category	4. Series CL: Contactor for general purpose application 9-105A AC3
Class	1. Contactors

Specifications

Series	Three-pole contactors from 9 to 105 A (AC3)
Control circuit	AC
Frequency Control Voltage: AC	50-60 Hz
Terminal type	Double clamp terminal
Max. operating current AC1 Non-inductive loads	60 A
Max. operating current AC3 Motors = 480V, 3-phase 50/60Hz	40 A
Electrical endurance: # operations AC3	2 x 10 ⁶
Type	For contactors type CL - D
Control Voltage: AC (50/60 Hz)	42 V
Admissible power AC3 220V, 230V	11 kW
Admissible power AC3 380V, 400V	18.5 kW
Admissible power AC3 415V, 440V	22 kW
Admissible power AC3 500V	25 kW
Package (pcs)	10
Utilization Category	AC3
Number of main poles	3 poles

Classifications

ETIM 5.0	EC000066
ETIM 6.0	EC000066

Dimensions

Weight	0.490 kg
--------	----------

Publications

Title	Publication No.	Publication Type
CONACL45T CONACL45 Total view	CONACL45T	Commercial Drawings
CONACL45R CONACL45 Rear view	CONACL45R	Commercial Drawings
CONACL45F CONACL45 Front view	CONACL45F	Commercial Drawings
CONACL45L CONACL45 Side view	CONACL45L	Commercial Drawings

Additional Documentation: Visit our [Publication Library](#) to find technical documentation, specifications, catalogues, promotional literature, 3D's,...