
Product datasheet Characteristics

NSYMD86

Symmetrical mounting chassis (6 rails)for enclosure dimensions H800xW600mm



Price*: 40.25 GBP



Main

Device application Multi-purpose Range Spacial Product or component type Chassis Accessory / separate part category Mounting accessory Type of rail Symmetrical DIN Mounting support Direct fixing on backstuds Step slide Spacer Range compatibility Spacial CRN Spacial S3D Spacial S3D Spacial S3X Thalassa PLM Device composition 2 upright Fixing elements	TTO TO	
Product or component type Accessory / separate part category Type of rail Mounting support Direct fixing on backstuds Step slide Spacer Range compatibility Spacial CRN Spacial S3D Spacial S3X Thalassa PLM Device composition Chassis Mounting accessory Mounting accessory Symmetrical DIN Direct fixing on backstuds Step slide Spacer Spacial CRN Spacial S3D Spacial S3D Spacial S3X Thalassa PLM	Device application	Multi-purpose
Accessory / separate part category Type of rail Symmetrical DIN Mounting support Direct fixing on backstuds Step slide Spacer Range compatibility Spacial CRN Spacial S3D Spacial S3X Thalassa PLM Device composition 2 upright Fixing elements	Range	Spacial
Type of rail Symmetrical DIN Mounting support Direct fixing on backstuds Step slide Spacer Range compatibility Spacial CRN Spacial S3D Spacial S3X Thalassa PLM Device composition 2 upright Fixing elements	Product or component type	Chassis
Mounting support Direct fixing on backstuds Step slide Spacer Range compatibility Spacial CRN Spacial S3D Spacial S3X Thalassa PLM Device composition 2 upright Fixing elements	Accessory / separate part category	Mounting accessory
Step slide Spacer Range compatibility Spacial CRN Spacial S3D Spacial S3X Thalassa PLM Device composition 2 upright Fixing elements	Type of rail	Symmetrical DIN
Spacial S3D Spacial S3X Thalassa PLM Device composition 2 upright Fixing elements	Mounting support	Step slide
Fixing elements	Range compatibility	Spacial S3D Spacial S3X
6 DIN rail	Device composition	, o
Quantity per set Set of 1	Quantity per set	Set of 1

Complementary

Ry fiving element	
Screwed on backstuds	
On step slides, type NSYSDCR, pitch 12.5 mm	<u>.</u>
Real : 739.3 mm Nominal : 800 mm	
Nominal : 600 mm Real : 550 mm	
Real: 30 mm	
	On step slides, type NSYSDCR, pitch 12.5 mm Real : 739.3 mm Nominal : 800 mm Nominal : 600 mm Real : 550 mm

Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 0940 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
	Product environmental	
Product end of life instructions	Need no specific recycling operations	

Warranty period	18 months	