

# 216RS6W



Ind. P&S#216RS6W



## General Information

Extended Product Type	216RS6W
Product ID	2CMA167149R1000
EAN	7392696671491
Catalog Description	Ind. P&S#216RS6W
Long Description	Surface socket-outlet, earthing sleeve position 6h, rated current 16A, IP67 watertight, 2-poles+earth, frequency 50-60 Hz, color code Blue

## Ordering

EAN	7392696671491
Minimum Order Quantity	1 piece
Country of Origin	Czech Republic (CZ)

## Dimensions

Product Net Width	99 mm
Product Net Height	172 mm
Product Net Length	115 mm
Product Net Depth / Length	172 mm
Product Net Weight	0.34 kg

## Container Information

Package Level 1 Width	135 mm
Package Level 1 Depth / Length	140 mm
Package Level 1 Height	200 mm
Package Level 1 Gross Weight	0.42 kg
Package Level 1 EAN	7392696671491
Package Level 1 Units	box 1 piece
Package Level 2 Units	174 piece

## Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Declaration	2CMC700005D0001
Environmental Information	2CMC000056M0000

RoHS Information	2CMC700005D0001_G
SEMKO Certificate	1613211
UL Certificate	2CMC700005D0001

## Additional Information

Additional Information	2P+E
Cable Cross-Section	1.5 ... 4 mm <sup>2</sup>
Cable Diameter	25 mm
Color	Blue
Connection Type	Screw Clamp
Degree of Protection	IP67 IP69
Enclosure Material	Thermoplastic polyester (PBT)
Frequency (f)	50 Hz 60 Hz
Function	Surface socket outlet
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#216RS6W
Mounting Holes	79.5x79.5
Number of Poles	3
Order Multiple	1 piece
Product Main Type	TRS
Product Name	Wall mounted socket
Protection Type	Watertight
Rated Current (I <sub>n</sub> )	16 A
Rated Voltage (U <sub>r</sub> )	200 ... 250 V
Recommended Screw Driver	PH2
RoHS Date	L23
Standards	IEC 60309-1 IEC 60309-2
Suitable For	Surface Socket Outlets
Suitable for Product Class	Industrial Plugs and Sockets

## Classifications

eClass	27440510
UNSPSC	39120000

## Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Surface Socket Outlets

