

# ZCKE67

limit switch head ZCKE - steel roller plunger reinforced



## Main

|                           |  |
|---------------------------|--|
| Range of product          | OsiSense XC  |
| Series name               | Standard format  |
| Product or component type | Limit switch head  |
| Device short name         | ZCKE   |
| Head type                 | Plunger head   |
| Product compatibility     | XCKJ   |
| Associated body           | ZCKJD37H29<br>ZCKJD39<br>ZCKJ1H29<br>ZCKJD39H7<br>ZCKJ6H7<br>ZCKJD31H7<br>ZCKJ11<br>ZCKJ4H29<br>ZCKJ8<br>ZCKJ5H7<br>ZCKJD31<br>ZCKJ7H7<br>ZCKJ2<br>ZCKJ5H29<br>ZCKJ6H29<br>ZCKJ1<br>ZCKJ11H7<br>ZCKJ7H29<br>ZCKJ9H7<br>ZCKJD39H29<br>ZCKJ7<br>ZCKJ8H29<br>ZCKJD37H7<br>ZCKJ6<br>ZCKJ4<br>ZCKJD35H29<br>ZCKJ21H29<br>ZCKJ9H29<br>ZCKJ41H7<br>ZCKJ11H29<br>ZCKJ41H29 |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

ZCKJD31H29  
 ZCKJ2H7  
 ZCKJ9  
 ZCKJD37  
 ZCKJ2H29  
 ZCKJ4H7  
 ZCKJ21H7  
 ZCKJ8H7  
 ZCKJ21  
 ZCKJ1H7  
 ZCKJ5  
 ZCKJD35H7  
 ZCKJD35  
 ZCKJ41

|                            |   |
|----------------------------|---|
| Movement of operating head | Linear  |
| Type of operator           | Roller plunger spring return metal (reinforced) |
| Type of approach           | Lateral approach 2 directions                   |

### Complementary

|                  |            |
|------------------|------------|
| Switch actuation | By 30° cam |
| Positive opening | With       |
| Head material    | Metal      |

### Environment

|                                       |                      |
|---------------------------------------|----------------------|
| Ambient air temperature for operation | -25...70 °C          |
| Ambient air temperature for storage   | -40...70 °C          |
| Environmental characteristic          | Standard environment |

### Offer Sustainability

|                                  |   |
|----------------------------------|---|
| Sustainable offer status         | Green Premium product   |
| RoHS (date code: YYWW)           | Compliant - since 0851 - Schneider Electric declaration of conformity<br><a href="#">Schneider Electric declaration of conformity</a> |
| REACH                            | Reference not containing SVHC above the threshold<br><a href="#">Reference not containing SVHC above the threshold</a>                |
| Product end of life instructions | Need no specific recycling operations   |

### Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|