







KEMPSTON CONTROLS

Honeywell

Product Type	MICRO SWITCH™ Toggle Switch				
Ampere/Voltage Range (Resistive Load)	0.75 A at 115 Vdc 0.5 A at 250 Vdc 0.5 A to 10 A at 0.5 Vac to 277 Vac 0.5 A to 15 A at 0.5 Vdc to 28 Vdc				
Circuitry	SPST				
Action	2 position				
Circuitry/Operating action	<table><thead><tr><th>Keyway Momentary Position</th><th>Opposite Keyway Position</th></tr></thead><tbody><tr><td></td><td></td></tr></tbody></table>	Keyway Momentary Position	Opposite Keyway Position		
Keyway Momentary Position	Opposite Keyway Position				
					
Mounting	Bushing 15/32 in				
Termination	Screw				
MIL Spec. Number	MS24523-30				
Lever Type	Standard				
UL/CSA	L192: 10 A-125, 250, 277 Vac; 1/4 Hp-125 Vac; 1/2 Hp-250, 277 Vac; 3 A-125 Vac "L"				
Comment	Silver cadmium oxide contacts				
Availability	Global				
UNSPSC Code	30211908				
UNSPSC Commodity	30211908 Toggle switches				
Series Name	TL				