## Product datasheet Characteristics

## XZCP0566L5

pre-wired connectors XZ - straight female - M8 - 3 pins - cable PUR 5m



Price\* : 12.66 GBP



#### Main

Accessory / separate part category	Cabling accessory
Accessory / separate part type	Pre-wired connectors
Series name	General purpose

### Complementary

Electrical connection	M8, 3 pins straight female connector	
Cable connector fixing	Screw-on	
Collar material	Metal	
Status LED	Without	
Cable length	5 m	
Cable outer diameter	5.2 mm	
Cable composition	3 x 0.34 mm <sup>2</sup>	
Wire insulation material	PUR	
[Ue] rated operational voltage	60 V AC 75 V DC	
[In] rated current	4 A	
Contact resistance	5000 μOhm	
Insulating resistance	1 GΩ	
Product weight	0.12 kg	

#### Environmen

Environment		<u>y</u> .
IP degree of protection	IP65 IP67 IP69K	or is transfer
Product certifications	CULus	
Ambient air temperature for operation	-4080 °C (static) -580 °C (flexing)	i. L

Ambient air temperature for storage	-4080 °C	
Offer Sustainability		
Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 0649 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
	Product Environmental Profile	
Product end of life instructions	Available	
	End of Life Information	


## Contractual warranty

Warranty period 18	8 months

# Product datasheet Dimensions Drawings

## XZCP0566L5

### **Dimensions**




## Product datasheet Connections and Schema

## XZCP0566L5

### Connections and Schemes

### Connector



BU: Blue BN: Brown BK: Black