







POIGNÉES/ HANDLE			PN7C PN12C Size 1	DSN24C Size 2	DN9C DSN37C Size 3	DS7C3 Size 4	DN20C Size 5		
POIGNÉE POLY TARAUDÉE (PE NON FOURNI)/POLY HANDLE WITHOUT CABLE GLAND (METRIC THREAD ENTRY)									
	0°	M20	511P0M20	512P0M20	513P0M20				Réf. +443
	0°	M25	511P0M25	512P0M25	513P0M25				Réf. +443
	0°	M32	511P0M32	512P0M32	513P0M32	514P0M32			Réf. +443
	0°	M40		512P0M40	513P0M40	514P0M40			Réf. +443
	0°	M50				514P0M50	515P0M50		Réf. +443
	0°	M63					515P0M63		Réf. +443
POIGNÉE MÉTAL TARAUDÉE (PE NON FOURNI)/METAL HANDLE WITHOUT CABLE GLAND (METRIC THREAD ENTRY)									
	0°	M20	591P0M20	592P0M20	593P0M20				Réf. +EMC
	0°	M25	591P0M25	592P0M25	593P0M25	594P0M25			Réf. +EMC
	0°	M32	591P0M32	592P0M32	593P0M32	594P0M32	595P0M32		Réf. +EMC
	0°	M40			593P0M40	594P0M40	595P0M40		Réf. +EMC
	0°	M50				594P0M50	595P0M50		
	0°	M63					595P0M63		

LÉGENDES DES OPTIONS D'ACCESSOIRES/LEGEND



Inclinaison/Angle



Taraudage ou serrage sur diamètre de câble/Threading



Option EMC/EMC option



HT 240° C



Éjection/ejection

INFOS +