9007R18 LIMIT SWITCH LEVER ARM C +OPTIONS



Main
Range

Range of product	9007
Series name	Severe duty
Product or component type	Limit switch lever
Device short name	9007T/FT
Associated head	9007AS9 9007T5S9 9007BS9 9007T10S9 9007NS9 9007CS9
Associated complete product	9007CS9 9007T 9007FT
Movement of operating head	Rotary
Type of operator	Cast zinc spring return roller without lever - offset: - roller and clamp only (use 9007R16 or 17)
Type of roller	1 steel optional position diameter: 19.05 mm - width: 6.35 mm
Type of approach	Lateral approach
	APPO /
Positive opening	Without
Complementary Switch actuation	By 30° cam
Complementary	
Complementary Switch actuation Net weight Environment	By 30° cam
Complementary Switch actuation	By 30° cam 0.05 kg
Complementary Switch actuation Net weight Environment Ambient air temperature for operation	By 30° cam 0.05 kg -2385 °C
Complementary Switch actuation Net weight Environment Ambient air temperature for operation Ambient air temperature for storage Environmental characteristic	By 30° cam 0.05 kg -2385 °C -2385 °C
Complementary Switch actuation Net weight Environment Ambient air temperature for operation Ambient air temperature for storage Environmental characteristic Packing Units	By 30° cam 0.05 kg -2385 °C -2385 °C Standard environment
Complementary Switch actuation Net weight Environment Ambient air temperature for operation Ambient air temperature for storage Environmental characteristic	By 30° cam 0.05 kg -2385 °C -2385 °C

Complementary

Switch actuation	By 30° cam
Net weight	0.05 kg

Environment

Environmental characteristic	Standard environment
Ambient air temperature for storage	-2385 °C
Ambient air temperature for operation	-2385 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	45.359 g

Offer Sustainability	PE101 P. 1	
Package 1 Length	16.387 cm	
Package 1 width	2.54 cm	
Package 1 Height	6.452 cm	

REACh Regulation	REACh Declaration
EU RoHS Directive	Not applicable, out of EU RoHS legal scope
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months