

# S2C-UA 230 DC



S2C-UA 230 DC - Undervoltage release



## General Information

|                       |  |
|-----------------------|--|
| Extended Product Type | S2C-UA 230 DC  |
| Product ID            | 2CSS200911R0010  |
| EAN                   | 8012542896708  |
| Catalog Description   | S2C-UA 230 DC - Undervoltage release   |
| Long Description      | The S2C-UA 230 DC undervoltage release has the function to protect the load in case of a voltage drop included between 70% and 35% of its rated value. Positive safety (device tripping when the voltage is disconnected) emergency stop by means of a button. Suitable for MCBs S200 series, RCCBs F200 series and RCBOs DS201, DS202C, DS200 series. It can be used with MCBs SN201 series by means of SN201-IH interface module. Rated voltage: 230V d.c. |

## Ordering

|                        |               |
|------------------------|---------------|
| EAN                    | 8012542896708 |
| Minimum Order Quantity | 1 piece       |
| Customs Tariff Number  | 85389099      |

## Dimensions

|                            |          |
|----------------------------|----------|
| Product Net Width          | 0.018 m  |
| Product Net Height         | 0.085 m  |
| Product Net Depth / Length | 0.074 m  |
| Product Net Weight         | 0.090 kg |

## Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Units          | 1 piece       |
| Package Level 1 Width          | 0.125 m       |
| Package Level 1 Height         | 0.035 m       |
| Package Level 1 Depth / Length | 0.11 m        |
| Package Level 1 Gross Weight   | 0.1 kg        |
| Package Level 1 EAN            | 8012542896708 |

## Environmental

|             |                                   |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

## Additional Information

|                            |   |
|----------------------------|---|
| Product Main Type          | S2C-UA  |
| Product Name               | Undervoltage release  |
| Suitable For               | S200, SN201, F200, DS201, DS202C, DS200   |
| Suitable for Product Class | Miniature Circuit Breakers MCBs<br>Residual Current Devices RCDs<br>Residual Current Breakers with Overload Protection RCBo |

## Certificates and Declarations (Document Number)

|                                   |                     |
|-----------------------------------|---------------------|
| Data Sheet, Technical Information | 2CSC400002D0209     |
| Declaration of Conformity - CE    | 9AKK106713A5575     |
| Environmental Information         | document not needed |
| Instructions and Manuals          | 9AKK107045A1514     |

## Classifications

|                            |  |
|----------------------------|--|
| ETIM 4                     | EC000042 - Miniature circuit breaker (MCB)                 |
| ETIM 5                     | EC001286 - Auxiliary contact unit for distribution board   |
| ETIM 6                     | EC001286 - Auxiliary contact unit for distribution board   |
| ETIM 7                     | EC001286 - Auxiliary device for distribution board devices |
| Object Classification Code | Q  |
| WEEE Category              | 5. Small Equipment (No External Dimension More Than 50 cm) |

## Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Miniature Circuit Breakers MCBs Accessories → Undervoltage Releases

