


# With electronic components

## with UL94V-0 polyamide insulating body

- for overlapped circuits
- possibility to perform cross-connections on both lower and upper levels (DAS.4/A and DAS. 4/B; other versions only on lower level)
- available in grey RAL 7042 and beige RAL 1001 colours



DAS.4/C terminal block


The /GR tag indicates the grey colour version.

grey version	DAS.4/.../GR
	Cat. No. DS...GR
beige version	DAS.4/...
	Cat. No. DS...
(Ex)i version	
TECHNICAL CHARACTERISTICS	
function / type	2-level component-holder
rated cross-section (mm <sup>2</sup> )	4
connecting capacity	
flexible (mm <sup>2</sup> )	0,2 ÷ 6
rigid (mm <sup>2</sup> )	0,2 ÷ 6
max. flexible with ferrule (mm <sup>2</sup> -ferrule type)	4 - WP40/16
rated voltage / rated current / gauge conf. to IEC 60947-7-1	630 V (*) / - / A4
rated voltage (Ex e) rated voltage (V)	-
rated impulse withstand voltage / pollution degree	8 kV / 3
insulation stripping length (mm)	9
tightening torque value (test / max) (Nm)	0,5 / 1,2
height / width / thickness TH/35 7,5 mm	62 / 64 / 6
height / width / thickness TH/35 15 mm	70 / 64 / 6
height / width / thickness G32	66 / 64 / 6


### APPROVALS

Approval referring to DAS.4 standard version


ACCESSORIES	Type	Cat. No.
End sections	grey	DAS/PT/GR DS101GR
	beige	DAS/PT DS101
	blue	-
Permanent cross connection (pre-assembled)	PM/41/2 poles	PM412
	PM/51/3 poles	PM513
	PM/51/5 poles	PM515
	PM/51/10 poles	PM510
Switchable cross connection	POS/43	POS43
Multiple common bar	PMP/58	PMP58
Shunting screw and sleeve	CPM/01	CPM01
Coloured partition	DFU/7	DU07..
Cross connection barrier	-	-
Test plug socket	PSD/A	PD001
Test plug	SDD/1	DD001
Modular test plug	-	-
End section for modular test plug	-	-
Numbering strip	-	-
Warning plate	-	-
Cover for cross-connection	PRP/5	PRP05
Marking tag	CNU/8/61	NU0861
End bracket	BTU for PR/DIN and PR/3	BT005
	BT/DIN/PO for PR/DIN only	BT001
	BT/3-BTO for PR/3 only	BT003-BT007
	PR/DIN/AC of steel	PR001
	PR/DIN/AS same with slots	PR004
	PR/DIN/AL of aluminium	PR002
	PR/3/AC for PR/DIN and PR/3	PR003
	PR/3/AS same with slots	PR005
Mounting rail according to IEC 60715 Std.		




Cat. No. DS111GR - DS111




Cat. No. DS112GR - DS112




Cat. No. DS113GR - DS113




Cat. No. DS114GR - DS114




Cat. No. DS115GR - DS115




Cat. No. DS119GR - DS119




Cat. No. DS130GR - DS130



Cat. No. DS120GR - DS120



Cat. No. DS128GR - DS128



Cat. No. DS129GR - DS129

(\*) The voltage and current ratings given for the various versions are based on the various type of components and to their connections.