



Circuit breaker size S3 For starter combination Rated current 75 A Short-circuit release 975 A Screw terminal Standard switching capacity !!!
 Phased-out product !!! Successor is SIRIUS 3RV2 Preferred successor type is >>3RV2331-4KC10<<

product brand name	SIRIUS
product designation	circuit breaker
design of the product	for starter combinations

General technical data

product extension auxiliary switch	Yes
power loss [W] for rated value of the current	
• at AC in hot operating state	38 W
• at AC in hot operating state per pole	12.7 W
surge voltage resistance rated value	6 000 V
protection class IP on the front	IP20
shock resistance	25g / 11 ms
mechanical service life (operating cycles) of the main contacts typical	50 000
continuous current rated value	75 A
Substance Prohibitance (Date)	07/01/2006

Ambient conditions

installation altitude at height above sea level maximum	2 000 m
ambient temperature	
• during operation	-20 ... +60 °C
• during storage	-50 ... +80 °C
• during transport	-50 ... +80 °C

Main circuit

number of poles for main current circuit	3
operating voltage	
• rated value	690 V
• at AC-3 rated value maximum	690 V
operational current at AC-3 at 400 V rated value	75 A
operating power at AC-3	
• at 400 V rated value	37 kW
operating frequency at AC-3 maximum	15 1/h

Auxiliary circuit

number of CO contacts for auxiliary contacts	0
--	---

Protective and monitoring functions

product function	
• ground fault detection	No
• phase failure detection	No
maximum short-circuit current breaking capacity (I_{cu})	
• at AC at 240 V rated value	100 kA
• at AC at 400 V rated value	50 kA
• at AC at 500 V rated value	8 kA
• at AC at 690 V rated value	5 kA










Short-circuit protection					
design of the overcurrent release and short-circuit release	magnetic				
Installation/ mounting/ dimensions					
mounting position	any				
fastening method	screw and snap-on mounting onto 35 mm DIN rail according to DIN EN 50022				
height	165 mm				
width	70 mm				
depth	174 mm				
required spacing with side-by-side mounting					
<ul style="list-style-type: none"> backwards at the side 	0 mm 0 mm				
Connections/ Terminals					
product component removable terminal for auxiliary and control circuit	No				
type of electrical connection					
<ul style="list-style-type: none"> for main current circuit for auxiliary and control circuit 	screw-type terminals with box terminals screw-type terminals				
arrangement of electrical connectors for main current circuit	front side				
type of connectable conductor cross-sections for main contacts					
<ul style="list-style-type: none"> solid stranded finely stranded with core end processing 	2x (2.5 ... 16 mm ²) 2x (10 ... 50 mm ²), 1x (10 ... 70 mm ²) 2x (2.5 ... 35 mm ²), 2.5 ... 50 mm ²				
Safety related data					
touch protection against electrical shock	finger-safe				
Certificates/ approvals					
General Product Approval	Declaration of Conformity				
 CCC	Confirmation	 UL	 EAC	 EG-Konf.	 UK CA
Test Certificates		Marine / Shipping			other
Type Test Certificates/Test Report	Special Test Certificate	 ABS	 RINA	 DNV-GL	Miscellaneous
other		Railway			
Confirmation	 VDE	Special Test Certificate			
Further information					
Information on the packaging https://support.industry.siemens.com/cs/ww/en/view/109813875					
Information- and Downloadcenter (Catalogs, Brochures,...) https://www.siemens.com/ic10					
Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mfb=3RV1341-4KC10					
Cax online generator http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mfb=3RV1341-4KC10					
Service&Support (Manuals, Certificates, Characteristics, FAQs,...) https://support.industry.siemens.com/cs/ww/en/ps/3RV1341-4KC10					

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)


http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RV1341-4KC10&lang=en


Characteristic: Tripping characteristics, I^2t , Let-through current

<https://support.industry.siemens.com/cs/ww/en/ps/3RV1341-4KC10/char>

Further characteristics (e.g. electrical endurance, switching frequency)

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RV1341-4KC10&objecttype=14&gridview=view1>





last modified:

11/21/2022