

S7D 1600 4p F F



S7D 1600 4p F F



General Information

Extended Product Type	S7D 1600 4p F F
Product ID	1SDA020890R1
EAN	8015644208905
Catalog Description	S7D 1600 4p F F
Long Description	CIRCUIT-BREAKER SWITCH-DISCONNECTOR ISOMAX S7D 1600 FOUR-POLE FIXED WITH FRONT TERMINALS CASE WITH TERMINALS

Ordering

EAN	8015644208905
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	385 mm
Product Net Height	325 mm
Product Net Length	440 mm
Product Net Depth / Length	0.1385 m
Product Net Weight	22 kg

Container Information

Package Level 1 Units	1 piece
Package Level 1 Height	325 mm
Package Level 1 Depth / Length	385 mm
Package Level 1 Gross Weight	44.5 kg
Package Level 1 EAN	8015644208905

Additional Information

Number of Poles	4
Power Loss	260 W
Product Main Type	SACE Isomax
Product Name	Moulded Case Circuit Breaker
Rated Current (I_n)	1600 A

Rated Operational Voltage	690 V AC
Standards	IEC-947-3
Sub-type	S7
Suitable For	Isomax S7
Suitable for Product Class	Isomax
Terminal Connection Type	Front
Test Voltage at Industrial Frequency for 1 Minute	3000 V
Version	Fixed

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	ITSCE-604050012
Declaration of Conformity - CE	1SDL000160R0051
Environmental Information	1SDL000168R0
Instructions and Manuals	ITSCE-601780061
RoHS Information	1SDL000193R0001

Classifications

ETIM 4	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 5	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 6	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
Object Classification Code	Q
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Isomax

Low Voltage Products and Systems → Circuit Breakers → Service → Replacements

