XZCP1965L5

pre-wired connectors XZ - elbowed female - 1/2"20 UNF - 3 pins - cable PUR 5m



Price*: 15.34 GBP



Main		
Accessory / sepa- rate part category	Cabling accessory	
Accessory / sepa- rate part type	Pre-wired connectors	
Series name	General purpose	

Complementary

Electrical connection	1/2"20 UNF, 3 pins elbowed female connector	
Cable connector fixing	Screw-on	
Collar material	Metal	
Status LED	Without	
Cable length	5 m	
Cable outer diameter	5.2 mm	
Cable composition	3 x 0.34 mm²	
Wire insulation material	PUR	
[Ue] rated operational voltage	250 V AC 300 V DC	
[In] rated current	4 A	
Contact resistance	5000 μOhm	
Insulating resistance	1 GΩ	
Product weight	0.18 kg	

Environment

IP degree of protection	IP67
Product certifications	CULus
Ambient air temperature for operation	-3590 °C (static) -590 °C (flexing)
Ambient air temperature for storage	-35100 °C


Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0649 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold
Product environmental profile	Available Product Environmental
Product end of life instructions	Available

Contractual warranty

Warranty period	18 months

Dimensions



L: Lenght of cable

Product data sheet Connections and Schema

XZCP1965L5

Connections and Schemes

Connectors

GN 1 3 2 RD/WH RD/BK

GN: Green RD/WRed/White RD/BIRed/Black

Product Life Status: Commercialised