Product datasheet Characteristics

XZCP0666L5

pre-wired connectors XZ - elbowed female - M8 -3 pins - cable PUR 5m



Price*: 13.42 GBP



Main

Accessory / separate part category	Cabling accessory
Accessory / separate part type	Pre-wired connectors
Series name	General purpose

Complementary

Main		
Main Accessory / separate part category	Cabling accessory	
	Pre-wired connectors	
Accessory / separate part type		
Series name	General purpose	
Complementary		
Electrical connection	Elbowed female connector M8, 3 pins	
Cable connector fixing	Screw-on	
Collar material	Metal	
Status LED	Without	
Cable length	5 m	
Cable outer diameter	5.2 mm	
Cable composition	3 x 0.34 mm²	
Wire insulation material	PUR	
[Ue] rated operational voltage	60 V AC	
	75 V DC	
[In] rated current	4 A	
Contact resistance	5000 μOhm	
Minimum insulating resistance	1 GΩ	
Net weight	0.12 kg	
Environment		
IP degree of protection	IP65	
	IP69K	
	IP67	
Product certifications	CULus	
Ambient air temperature for operation	-4080 °C static	
	-580 °C flexing	

Environment

Environment		. <u>u</u>
IP degree of protection	IP65 IP69K IP67	o istatical in the control of the co
Product certifications	CULus	يَّ -
Ambient air temperature for operation	-4080 °C static -580 °C flexing	L

Ambient air temperature for storage	-4080 °C	
0.50		
Offer Sustainability		

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End of Life Information	


Contractual warranty

Warranty	18 months

Product datasheet Dimensions Drawings

XZCP0666L5

Dimensions




L: Lenght of cable

Product datasheet Connections and Schema

XZCP0666L5

Connections and Schemes

Connector



BU: Blue BN: Brown BK: Black