SIEMENS

Data sheet 5SV8111-4KK

Modular residual current device Type B, 24 V DC,LCD, IDN 30 mA 1A, 0 2000 Hz $\,$



Model	
Product brand name	SENTRON
Product designation	Modular RCCB device
Design of the product	Digital, type B
Protection class IP / at connection all terminals	IP20
Overvoltage category	III
Control current	
Control supply voltage	
at DC / rated value / minimum	9.6 V
• at DC / rated value / maximum	94 V
Auxiliary circuit	
Number of CO contacts / for auxiliary contacts	2
Product function	
Product function / Fault storage	Yes
Connections	
Type of electrical connection	screw-type terminals
Mechanical Design	

Height	85 mm
Width	36 mm
Depth	64 mm
Mounting type	standard rail
Net weight	150 g
Material / of the enclosure	PC
Degree of pollution	3
Ambient temperature	
 during operation / minimum permissible 	-25 °C
 during operation / maximum permissible 	55 °C

Waste electronic equipment must not be disposed as unsorted municipal waste, e.g. household waste. For disposing the waste electronic equipment it is necessary to observe the current local national/international regulations.



Declaration of Conformity

other



Miscellaneous

Information- and Downloadcenter (Catalogs, Brochures,...)

http://www.siemens.com/lowvoltage/catalogs

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SV8111-4KK

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/5SV8111-4KK

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...) http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SV8111-4KK

CAx-Online-Generator

http://www.siemens.com/cax

Tender specifications

http://www.siemens.com/specifications