

PRODUCT-DETAILS

CM-IWS.1S

CM-IWS.1S Insulation monitoring relay 1c/o, 1-100kOhm, 24-240VAC/DC



General Information

Extended Product Type	CM-IWS.1S
Product ID	1SVR730660R0100
EAN	4016779852609
Catalog Description	CM-IWS.1S Insulation monitoring relay 1c/o, 1-100kOhm, 24-240VAC/DC
Long Description	The CM-IWS.1S serves to monitor insulation resistance in accordance with IEC 61557-8 in unearthed IT AC systems, IT AC systems with galvanically connected DC circuits, or unearthed IT DC systems with a voltage up to 250 V AC and 300 V DC. It can be configured to the requirements of the applications and therefore used multi-functional.

Ordering

EAN	4016779852609
Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

Popular Downloads

Data Sheet, Technical Information	2CDC112195D0201
Instructions and Manuals	1SVC730550M0001
CAD Dimensional Drawing	2CDC001079B0201

Dimensions

Product Net Width	22.5 mm
Product Net Height	85.6 mm
Product Net Depth / Length	103.7 mm
Product Net Weight	0.148 kg

Technical

Function	Unearthed AC systems Unearthed DC systems Unearthed mixed AC / DC systems Up to 250 V AC Up to 300 V DC
Measuring Range	1 ... 100 kΩ
Rated Control Supply Voltage (U_s)	24 ... 240 V AC/DC
Rated Frequency (f)	Measuring Circuit 15 ... 400 Hz
Output	1 c/o (SPDT) contact
Terminal Type	Screw Terminals
Rated Operational Current AC-12 (I_{θ})	(230 V) 4 A
Rated Operational Current AC-15 (I_{θ})	(230 V) 3 A
Rated Operational Current DC-12 (I_{θ})	(24 V) 4 A
Rated Operational Current DC-13 (I_{θ})	(24 V) 2 A
Minimum Switching Capacity	24 V 10 mA
Rated Impulse Withstand Voltage (U_{imp})	Measuring Circuit / Output Circuit 6 kV Supply Circuit / Measuring Circuit 6 kV Supply Circuit / Output Circuit 6 kV
Rated Insulation Voltage (U_i)	Measuring Circuit / Output Circuit 300 V Supply Circuit / Measuring Circuit 300 V Supply Circuit / Output Circuit 300 V
Degree of Protection	Housing IP50 Terminals IP20
Overvoltage Category	III
Pollution Degree	3
Short-Circuit Protective Devices	Output Circuit NC - F Type Fuses 6 A Output Circuit NO - F Type Fuses 10 A
System Leakage Capacitance (C_E)	10 μF
Electrical Durability	AC-12 100000 cycle
Mechanical Durability	30000000 cycle
Connecting Capacity	Flexible with Ferrule 1x 0.5 ... 2.5 mm ² Flexible with Ferrule 2x 0.5 ... 1.5 mm ² Flexible with Insulated Ferrule 1x 0.5 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.5 ... 1.5 mm ² Flexible 1x 0.5 ... 2.5 mm ² Flexible 2x 0.5 ... 1.5 mm ² Rigid 1x 0.5 ... 4 mm ² Rigid 2x 0.5 ... 2.5 mm ²
Tightening Torque	0.6 ... 0.8 N·m
Wire Stripping Length	8 mm
Mounting Position	1 ... 6

Mounting on DIN Rail TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715

Standards	CAN/CSA C22.2 No.14 IEC/EN 63000 IEC/EN 61326-2-4 IEC/EN 61557-1 IEC/EN 61557-8 UL 508
-----------	---

Technical UL/CSA

Maximum Operating Voltage UL/CSA	Output Circuit 300 V AC
Contact Rating UL/CSA	B300
Connecting Capacity UL/CSA	Flexible 1x 18-14 AWG Flexible 2x 18-16 AWG Rigid 1x 20-12 AWG Rigid 2x 20-14 AWG
Tightening Torque UL/CSA	7.08 in-lb
Pilot Duty UL/CSA	B300
Flammability According to UL94	V-0

Environmental

Ambient Air Temperature	Operation -25 ... +60 °C Storage -40 ... +85 °C
Maximum Operating Altitude Permissible	Without Derating 2000 m
RoHS Status	Following EU Directive 2011/65/EU

Certificates and Declarations (Document Number)

CB Certificate	CB_DK-30302-A1-UL
CCC Certificate	CCC_2010010303438770
CQC Certificate	CQC2010010303438770
cULus Certificate	cULus508_20120727-E140448
Declaration of Conformity - CCC	2020980303000184
Declaration of Conformity - CE	1SVD981011-00
Declaration of Conformity - UKCA	1SVD981011-10
DNV GL Certificate	DNV_GL_TAA000017C
EAC Certificate	EAC_RU_C-DE.ME77.B.03424
Instructions and Manuals	1SVC730550M0001
RoHS Information	1SVD981011-00

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	97 mm
Package Level 1 Depth / Length	30 mm
Package Level 1 Height	109 mm
Package Level 1 Gross	0.173 kg

Weight

Package Level 1 EAN	4016779852609
---------------------	---------------

Classifications

Object Classification Code	B
ETIM 7	EC001444 - Insulation and earth fault monitoring relay
ETIM 8	EC001444 - Insulation and earth fault monitoring relay
ETIM 9	EC001444 - Insulation and earth fault monitoring relay
eClass	V11.0 : 27371807
UNSPSC	39122331
E-Number (Finland)	2712260
E-Number (Sweden)	3860655

Categories

Low Voltage Products and Systems → Control Products → Electronic Relays and Controls → Insulation Monitors

