

Data sheet

Commercial Art.No.: G5.536.0103.1

Distributor MST32I3V 2P1S25 01 BLC1

MST32i3 SPUR (tap off fused with 10 A) , 3 pole, cable length 1.0 m, cross section 2.5 mm², cable type H05Z1Z1/LSOH, coding C1: 250 V, coding color light blue, strain relief color black, color of housing grey



Technical data

General

Rated current	32 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	2
Mechanical coding	Code 1
Lockable	self-locking (unlocking by tool)
Color of coding/ contact carrier	Blue
Marking of poles	L, N, PE

Lead

Model	Spur
Microfuse (6,3x25 mm)	10 A
Drop	Metal conduit 16 mm
No. Of poles on drop	3
Cross section of drop	2.5 mm²
Termination of drop	free end
Length of drop	1 m
Length of open end	1 m
Stripping length of drop	10 mm
Design of conductor ends	Ultrasonically compressed wire ends
Color of coding pin	sky blue (C1)
Wiring system	
Internal cross section	

Model

Number of inputs	1
Number of outputs	2
Type of fastening	Yes
Degree of protection (IP)	IP20
Type of distributor	Spur

Material

Housing material

Polyamide

Halogen free	Yes
Contact material	CuZn
Fire load	0 kWh
Insulation components continuous temperature	100 °C
Surface finish	Silver-plated

Classification

ECLASS 8.1	27440603
ETIM 7.0	EC002567
ETIM 6.0	EC002567
ETIM 5.0	EC002567
ETIM 4.0	EC002567