

S402M-UCC0.5



S402M-UCC0.5 Miniature Circuit Breaker

General Information

Extended Product Type	S402M-UCC0.5
Product ID	2CCS562001R1984
EAN	7612270109913
Catalog Description	S402M-UCC0.5 Miniature Circuit Breaker
Long Description	MCB ,2P,UCC,0.5A,50kA,SMISSLINE

Ordering

EAN	7612270109913
Minimum Order Quantity	1 piece
Customs Tariff Number	85363020

Dimensions

Product Net Width	36 mm
Product Net Height	91 mm
Product Net Length	75 mm
Product Net Depth / Length	75 mm
Product Net Weight	285 g

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	100 mm
Package Level 1 Height	91 mm
Package Level 1 Depth / Length	185 mm
Package Level 1 Gross Weight	285 g
Package Level 1 EAN	7612270109913

Environmental

RoHS Status	Following EU Directive 2002/95/EC August 18, 2005 and amendment
-------------	---

Additional Information

Frequency (f)	50 ... 60 Hz
Number of Poles	2
Number of Protected Poles	2
Power Loss	1.59 W
Product Main Type	S400
Product Name	Miniature Circuit Breaker
Rated Current (I_n)	0.5 A
Rated Voltage (U_r)	440 V DC
Rated Operational Voltage	440 V DC 220 V DC 240 / 415 V AC
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu})	(440 V DC) 25 kA
RoHS Date	20170426
Standards	IEC/EN 60947-2
Tripping Characteristic	UC-C

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	2CCC451059C0203-REV-B
Declaration of Conformity - CE	2CCC451034D0201
Environmental Information	2CCY000200D0219
Instructions and Manuals	2CCC451019M0111
RoHS Information	2CCC413008D0206
Dimension Diagram	2CCC451028C0202

Classifications

ETIM 4	EC000042 - Miniature circuit breaker (MCB)
ETIM 5	EC000042 - Miniature circuit breaker (MCB)
ETIM 6	EC000042 - Miniature circuit breaker (MCB)
ETIM 7	EC000042 - Miniature circuit breaker (MCB)
Object Classification Code	FC
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Plug-in Distribution Systems

