

T5S400 MCP-UL/CSA PR221DS-I

In=400 3p FF

T5S400 MCP-UL/CSA PR221DS-I In=400 3p FF



General Information

Extended Product Type	T5S400 MCP-UL/CSA PR221DS-I In=400 3p FF
Product ID	1SDA059463R1
EAN	8015644618452
Catalog Description	T5S400 MCP-UL/CSA PR221DS-I In=400 3p FF
Long Description	C.BREAKER TMAX T5S 400 MCP UL/CSA FIXED THREE-POLE WITH FRONT TERMINALS AND MAGNETIC RELEASE IN AC PR221DS-I Iu 400 A

Ordering

EAN	8015644618452
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	140 mm
Product Net Height	205 mm
Product Net Depth / Length	103.5 mm
Product Net Weight	3.25 kg

Container Information

Package Level 1 EAN	8015644618452
---------------------	---------------

Additional Information

Mechanical Durability	20000 cycle 120 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 16,5 W
Product Main Type	SACE Tmax T
Product Name	Moulded Case Circuit Breaker
Product Type	CB
Rated Current (I_n)	Main Circuit 400 A
Rated Impulse Withstand Voltage (U_{imp})	8 kV 1000 V

Rated Insulation Voltage (U_i)

Rated Operational Voltage	600 V AC
---------------------------	----------

Rated Ultimate Short-Circuit Breaking Capacity (I_{cu})	(240 V AC) 100 kA (480 V AC) 35 kA (600 V AC) 25 kA (500 V DC) 2 Poles in Series 35 kA (600 V DC) 3 Poles in Series 25 kA
---	---

Rated Uninterrupted Current (I_u)	400 A
---------------------------------------	-------

Release Type	EL
--------------	----

Standards	UL
-----------	----

Sub-type	T5
----------	----

Suitable For	T5
--------------	----

Suitable for Product Class	Moulded Case Circuit Breakers
----------------------------	-------------------------------

Terminal Connection Type	Fixed Circuit-Breakers Front
--------------------------	---------------------------------

Test Voltage Max (U_{test})	3500 V
---------------------------------	--------

Version	F
---------	---

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	9AKK105713A5947
-----------------------------------	-----------------

Declaration of Conformity - CE	1SDL000165R0005
--------------------------------	-----------------

GL Certificate	1SDL000163R0062
----------------	-----------------

Instructions and Manuals	1SDC210023D0201
--------------------------	-----------------

Classifications

ETIM 6	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
--------	---

ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
--------	--

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
---------------	--

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax T

