

PSEN in1n

545003



To be discontinued, last order date 31.05.2018. Possible replacement 540003 (PSEN cs1.1n / PSEN cs1.1)

***** Bitte beachten: Änderung der sicherheitstechnischen Daten (de) Please note: Change of safety-related data (en) PL Kat. SIL PFH Alt - Old e 4 3 2,69e-9 Neu - New d 2 2 1,87e-8 Bitte beachten sie die überarbeitete Bedienanleitung See the attached revised operating manual [https://www.pilz.com/eshop/catalog/query/\(layout=7_72_89_88&uiarea=0\)/.do?query=545003&searchTypeOptions=shop#Operating Manual-de](https://www.pilz.com/eshop/catalog/query/(layout=7_72_89_88&uiarea=0)/.do?query=545003&searchTypeOptions=shop#Operating Manual-de) *****

Technical details

Approvals:	CE;cULus Listed;TÜV
Number of OSSD outputs:	2
Unit for supply voltage output:	500 mA
Connection type:	M12
Supply voltage (V):	24,0
Supply voltage type:	DC
Power consumption DC:	1.5 W
Assured switching distance:	12.5 mm
Assured release distance:	45.0 mm
Protection type, housing:	IP67
Width dimension:	40.0 mm
Height dimension:	75.0 mm
Depth dimension:	40.0 mm
Gross weight:	180 g
Net weight:	155 g
Ambient temperature:	-10 - 60 °C

Accessories



630297

PSEN op cable axial M12 5-pole 30m



630310

PSEN op cable axial M12 5-pole 3m



630311

PSEN op cable axial M12 5-pole 5m



630312

PSEN op cable axial M12 5-pole 10m



630347

PSEN op cable angle M12 5-pole 3m



630348

PSEN op cable angle M12 5-pole 5m



630349

PSEN op cable angle M12 5-pole 10m



630350

PSEN op cable angle M12 5-pole 30m

Optional accessories



380208

PSS67 Cable M12sf M12sm, 3m



380209

PSS67 Cable M12sf M12sm, 5m



380210

PSS67 Cable M12sf M12sm, 10m



380211

PSS67 Cable M12sf M12sm, 30m



380212

PSS67 Cable M12af M12am, 3m



380213

PSS67 Cable M12af M12am, 5m



380214

PSS67 Cable M12af M12am, 10m



380215

PSS67 Cable M12af M12am, 30m



773600

PDP67 F 8DI ION



380220

PSS67 cable M12-5sf, M12-5sm, 20m