

T5N 400 UL/CSA PR221DS-LS/I 400 2p F F



T5N 400 UL/CSA PR221DS-LS/I 400 2p F F

General Information

Extended Product Type	T5N 400 UL/CSA PR221DS-LS/I 400 2p F F
Product ID	1SDA064135R1
EAN	8015644669966
Catalog Description	T5N 400 UL/CSA PR221DS-LS/I 400 2p F F
Long Description	C.BREAKER TMAX T5N 400 UL/CSA FIXED TW0-POLE WITH FRONT TERMINALS AND SOLID-STATE RELEASE IN AC PR221DS-LS/I R 400

Ordering

EAN	8015644669966
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	140 mm
Product Net Height	205 mm
Product Net Depth / Length	103.5 mm
Product Net Weight	3.25 kg

Container Information

Package Level 1 EAN	8015644669966
---------------------	---------------

Additional Information

Mechanical Durability	20000 cycle 120 cycles per hour
Number of Poles	2
Product Main Type	SACE Tmax T
Product Name	Moulded Case Circuit Breaker
Product Type	CB
Rated Current (I_n)	Main Circuit 400 A
Rated Impulse Withstand Voltage (U_{imp})	8 kV
Rated Insulation Voltage (U_i)	1000 V

Rated Operational Voltage	600 V AC
Rated Uninterrupted Current (I _u)	400 A
Release Type	EL
Standards	UL
Sub-type	T5
Suitable For	T5
Suitable for Product Class	Moulded Case Circuit Breakers
Terminal Connection Type	Fixed Circuit-Breakers Front
Version	F

Certificates and Declarations (Document Number)

Instructions and Manuals	1SDC210023D0201
--------------------------	-----------------

Classifications

ETIM 6	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax T

