



Technical Characteristics

Range on Increasing Pressure	20 to 65 PSIG
Action	Standard Action
Application	To control electrically driven water pumps
Actuator Type	Diaphragm
Approvals	UL Listed File: E12158 CKN NKPZ - CSA Certified File: LR25490
Contact Arrangement	DPST
Enclosure Rating	NEMA 1
Flange Material	Zinc Plated Steel
Depth	2.78 Inches
Marketing Trade Name	Pumptrol
Enclosure Type	General Purpose (Indoor)
Diaphragm	Nitrile (Buna N)
Differential	15 to 30 PSIG
Differential Type	Adjustable
Height	2.80 Inches
Horsepower Rating (3-Phase)	2HP@115VAC - 3HP@230VAC - 1HP@460/575VAC
Horsepower Rating (1-Phase)	1.5HP@115VAC - 2HP@230VAC
Mounting Type	Bracket
Maximum Allowable Pressure	220 PSIG
Maximum Voltage Rating	575VAC
Weight	1.13 Pounds
Number of Poles	2-Pole
Pressure Connection	0.25 Inch NPSF
Pressure Setting	20 to 40 PSIG
Range on Decreasing Pressure	10 to 45 PSIG
Terminal Type	Screw Clamp
Type	F
Width	3.76 Inches

Shipping and Ordering

Category	21534 - Pressure Switches, Commercial, Individual Pack, Type FSG, FYG, FSW, FYW & FRG
Discount Schedule	CP7I

Generated: 06/23/2011 09:42:05

GTIN	00785901559245
Package Quantity	50
Weight	0.87 lbs.
Availability Code	Stock Item: This item is normally stocked in our distribution facility.
Returnability	Y
Country of Origin	MX

As standards, specifications, and designs change from time to time, please ask for confirmation of the information given in this document.