



Analog output module XI/ON, 24 V DC, 2AO (0/4 to 20mA)

Part no. XN-2AO-I(0/4...20MA)
Catalog No. 140146
EL-Nummer (Norway) 4520643

Delivery program

Function			XI/ON I/O modules
Function			XN Slice module
Short Description			2 Analog outputs 0/4 to 20 mA
For use with			XN-S3T-SBB XN-S3S-SBB

Technical data

General

Standards				EN 61000-6-2 EN 61000-6-4 EN 61131-2
Potential isolation				Yes, through optocoupler
Ambient temperature				
Ambient temperature, operation			°C	0 - +55
Storage, transport	9		°C	-25 - +85
Relative humidity				
Relative humidity				5 - 95 % (indoor), Level RH-2, no condensation (for storage at 45°C)
Ambient conditions, mechanical				
Degree of Protection				IP20
Harmful gases			ppm	SO ₂ : 10 (rel. humidity < 75%, no condensation) H ₂ S: 1.0 (rel. humidity < 75 %,no condensation)
Vibration resistance, operating conditions				according to IEC/EN 60068-2-6
Mechanical shock resistance			g	according to IEC 60068-2-27
Continuous shock resistance (IEC/EN 60068-2-29)				According to IEC 60068-2-29
Drop and topple				According to IEC 60068-2-31, free fall according to IEC 60068-2-32
Electromagnetic compatibility (EMC)				
ESD		Air/contact discharge	kV	EN 61000-4-2
Electromagnetic fields		(0.08...1) / (1,4...2) / (2...2,7) GHz	V/m	EN 61100-4-2
Burst				EN 61100-4-4
Surge				EN 61100-4-5
Radiated RFI			V	EN 61100-4-6
Emitted interference (radiated, high frequency)		(30...230 MHz) / (230...1000 MHz)	dB	EN 55016-2-3
Voltage fluctuations/voltage dips				EN 61131-2
Type test				to EN 61131-2
Approvals				CE, cULus
Other technical data (sheet catalogue)				Technical Data

Analog input modules

Measured variables				Current
Channels			Number	2

Rated voltage through supply terminal	U_L		24 V DC
Rated current consumption from supply terminal	I_L	mA	50
Rated current consumption from module bus	I_{MB}	mA	≤ 40
Heat dissipation		W	normally 1
Offset error		%	0.1
Basic error limit at 23 °C		%	0.2
Temperature coefficient			150 ppm/°C of full scale
Measured value representation			16-bit signed integer 12-bit full range left-justified

Analog output modules

Measured variables			Current
Channels		Number	2
Rated voltage through supply terminal	U_L		24 V DC
Rated current consumption from supply terminal	I_L	mA	50
Rated current consumption from module bus	I_{MB}	mA	≤ 40
Heat dissipation		W	normally 1
Output current		mA	0/4 - 20
Load resistance			
Resistive load		Ω	< 450
Inductive load		h	< 0.001
Transfer frequency		Hz	200
Offset error		%	0.1
Basic error limit at 23 °C		%	0.2
Temperature coefficient			150 ppm/°C of full scale
Settling time			
Resistive load		ms	2
Inductive load		ms	2
Capacitive load		ms	0.5
Measured value representation			16-bit signed integer 12-bit full range left-justified

Digital outputs

Channels		Number	2
Rated voltage through supply terminal	U_L		24 V DC
Rated current consumption from the supply terminal (at load current = 0 mA)	I_L	mA	50
Rated current consumption from module bus	I_{MB}	mA	≤ 40
Power loss	P	W	Normally 1
Resistive load		Ω	< 450
Inductive load		h	< 0.001

Digital inputs

Channels		Number	2
Rated voltage through supply terminal	U_L		24 V DC
Rated current consumption from supply terminal	I_L	mA	50
Rated current consumption from module bus	I_{MB}	mA	≤ 40
Heat dissipation		W	normally 1

Relay modules

Rated voltage through supply terminal	U_L		24 V DC
Rated current consumption from supply terminal	I_L	mA	50
Rated current consumption from module bus	I_{MB}	mA	≤ 40
Power loss	P	W	Normally 1

Power supply module

Rated voltage through supply terminal	U_L		24 V DC
Rated current consumption from supply terminal	I_L	mA	50
Rated current consumption from module bus	I_{MB}	mA	≤ 40
Power loss	P	W	1

Counter module

Channels		Number	2
----------	--	--------	---

Rated voltage through supply terminal	U_L		24 V DC
Rated current consumption from supply terminal	I_L	mA	50
Rated current consumption from module bus	I_{MB}	mA	≤ 40
Heat dissipation		W	normally 1

Measuring modes

Temperature coefficient			150 ppm/°C of full scale
Number of parameter bits			3 (per channel)

Interfaces

Rated voltage through supply terminal	U_L		24 V DC
Rated current consumption from supply terminal	I_L	mA	50
Rated current consumption from module bus	I_{MB}	mA	≤ 40
Power loss	P	W	Normally 1
Number of parameter bytes			3 (per channel)

Design verification as per IEC/EN 61439

Technical data for design verification			
Rated operational current for specified heat dissipation	I_n	A	0
Heat dissipation per pole, current-dependent	P_{vid}	W	0
Equipment heat dissipation, current-dependent	P_{vid}	W	0
Static heat dissipation, non-current-dependent	P_{vs}	W	1
Heat dissipation capacity	P_{diss}	W	0
Operating ambient temperature min.		°C	0
Operating ambient temperature max.		°C	55
Degree of Protection			IP20
IEC/EN 61439 design verification			
10.2 Strength of materials and parts			
10.2.2 Corrosion resistance			
			Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures			
			Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat			
			Meets the product standard's requirements.
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects			
			Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation			
			Meets the product standard's requirements.
10.2.5 Lifting			
			Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact			
			Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions			
			Meets the product standard's requirements.
10.3 Degree of protection of ASSEMBLIES			
			Meets the product standard's requirements.
10.4 Clearances and creepage distances			
			Meets the product standard's requirements.
10.5 Protection against electric shock			
			Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components			
			Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections			
			Is the panel builder's responsibility.
10.8 Connections for external conductors			
			Is the panel builder's responsibility.
10.9 Insulation properties			
10.9.2 Power-frequency electric strength			
			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			
			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			
			Is the panel builder's responsibility.
10.10 Temperature rise			
			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating			
			Is the panel builder's responsibility.
10.12 Electromagnetic compatibility			
			Is the panel builder's responsibility.
10.13 Mechanical function			
			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 8.0

Programmable logic controllers PLC (EG000024) / Fieldbus, decentr. periphery - analogue I/O module (EC001596)
Electric engineering, automation, process control engineering / Control / Field bus, decentralized peripheral / Field bus, decentralized peripheral - analogue I/O module (ec@ss10.0.1-27-24-26-01 [BAA061014])

Supply voltage AC 50 Hz	V	0 - 0
Supply voltage AC 60 Hz	V	0 - 0
Supply voltage DC	V	20.4 - 28.8
Voltage type of supply voltage		DC
Input, current		No
Input, voltage		No
Input, resistor		No
Input, resistance thermometer		No
Input, thermocouple		No
Input signal, configurable		No
Resolution of the analogue inputs	Bit	0
Output, current		Yes
Output, voltage		No
Output signal configurable		Yes
Resolution of the analogue outputs	Bit	16
Number of analogue inputs		0
Number of analogue outputs		2
Analogue inputs configurable		Yes
Analogue outputs configurable		Yes
Number of HW-interfaces industrial Ethernet		0
Number of interfaces PROFINET		0
Number of HW-interfaces RS-232		0
Number of HW-interfaces RS-422		0
Number of HW-interfaces RS-485		0
Number of HW-interfaces serial TTY		0
Number of HW-interfaces parallel		0
Number of HW-interfaces Wireless		0
Number of HW-interfaces USB		0
Number of HW-interfaces other		1
Supporting protocol for TCP/IP		No
Supporting protocol for PROFIBUS		No
Supporting protocol for CAN		No
Supporting protocol for INTERBUS		No
Supporting protocol for ASI		No
Supporting protocol for KNX		No
Supporting protocol for Modbus		No
Supporting protocol for Data-Highway		No
Supporting protocol for DeviceNet		No
Supporting protocol for SUCONET		No
Supporting protocol for LON		No
Supporting protocol for PROFINET IO		No
Supporting protocol for PROFINET CBA		No
Supporting protocol for SERCOS		No
Supporting protocol for Foundation Fieldbus		No
Supporting protocol for EtherNet/IP		No
Supporting protocol for AS-Interface Safety at Work		No
Supporting protocol for DeviceNet Safety		No
Supporting protocol for INTERBUS-Safety		No
Supporting protocol for PROFIsafe		No
Supporting protocol for SafetyBUS p		No
Supporting protocol for other bus systems		Yes
Radio standard Bluetooth		No
Radio standard Wi-Fi 802.11		No
Radio standard GPRS		No
Radio standard GSM		No

Radio standard UMTS			No
IO link master			No
System accessory			Yes
Degree of protection (IP)			IP20
Degree of protection (NEMA)			1
Type of electric connection			Screw-/spring clamp connection
Fieldbus connection over separate bus coupler possible			Yes
Rail mounting possible			Yes
Wall mounting/direct mounting			No
Front built-in possible			No
Rack-assembly possible			No
Suitable for safety functions			No
SIL according to IEC 61508			None
Performance level according to EN ISO 13849-1			None
Appendant operation agent (Ex ia)			No
Appendant operation agent (Ex ib)			No
Explosion safety category for gas			None
Explosion safety category for dust			None
Width		mm	12.6
Height		mm	74.1
Depth		mm	55.4

Approvals

Product Standards			UL 508; CSA-C22.2 No. 142; IEC/EN 6113-2; CE marking
UL File No.			E205091
UL Category Control No.			NRAQ, NRAQ7
CSA File No.			UL report applies to both US and Canada
CSA Class No.			2252-01, 2252-81
North America Certification			UL recognized, certified by UL for use in Canada
Specially designed for North America			No
Current Limiting Circuit-Breaker			No
Degree of Protection			IEC: IP20, UL/CSA Type: -

Dimensions



Dimensions

Additional product information (links)

Manual XI/ON analog I/O modules MN05002011Z

Handbuch XI/ON analoge E/A-Module
MN05002011Z - Deutsch

https://es-assets.eaton.com/DOCUMENTATION/AWB_MANUALS/MN05002011Z_DE.pdf

Manual XI/ON analog I/O modules
MN05002011Z - English

https://es-assets.eaton.com/DOCUMENTATION/AWB_MANUALS/MN05002011Z_EN.pdf

Technical Data

<http://ecat.moeller.net/flip-cat/?edition=HPLEN&startpage=14.111>