

## AV25LKX11.5U-GB215

- left-hand model
- Metal enclosure
- Fail-safe locking system
- for 2-leaf doors
- authorised for use in passenger elevators
- Manual release by means of M5 triangular key

## Data

### Ordering data

Product type description	AV25LKX11.5U-GB215
Article number (order number)	103016463
EAN (European Article Number)	4030661508597
eCl@ss number, version 9.0	27-27-26-03
eCl@ss number, version 11.0	27-27-26-03
eCl@ss number, version 12.0	27-27-26-03
ETIM number, version 7.0	EC002593
ETIM number, version 6.0	EC002593

### Approvals - Standards

Certificates	TÜV EAC
--------------	------------

## General data

Standards	EN 81-20 EN 81-50
Enclosure material	Light alloy die-casting
Material of the contacts, electrical	Silver
Material of the latching bolt	Brass
Gross weight	1,390 g

## General data - Features

Manual release	Yes
With fail-safe locking system (Y/N)	Yes
Safety functions	Yes
Number of door leafs	2
Number of safety contacts	2

## Mechanical data

Actuating element	Pull strap
Orientation / Alignment	left-hand model
Mounting	rear-side mounting holes
Permanent magnet	Ceramic oxide magnets with high coercive field strength

## Mechanical data - Connection technique

Cable entry	without cable gland
-------------	---------------------

## Mechanical data - Dimensions

Width	285 mm
Height	80 mm

Depth	36 mm
Diameter of the latching bolt	18 mm
X-dimension of the latching bolt	11.5 mm
Note (X-dimension of the latching bolt)	The entire locking bolt length results from the prescribed insertion depth of the locking bolt into the door leaf of 21 mm and dimension X. Dimension X represents the distance between the bottom of the enclosure of the door closing device and the top of the door.
Latching bolt bevelling, bottom	45 °

## Ambient conditions

Degree of protection	IP20
Ambient temperature, minimum	-15 °C
Ambient temperature, maximum	+70 °C

## Ambient conditions - Insulation values

Rated insulation voltage $U_i$	400 VAC
Rated impulse withstand voltage $U_{imp}$	6 kV

## Electrical data

Thermal test current	10 A
Utilisation category AC-15	230 VAC
Utilisation category AC-15	2 A
Utilisation category DC-13	200 VDC
Utilisation category DC-13	2 A
Switching element	NC contact, NO contact

Switching principle    Slow action

## Note

Note (Manual release)      For manual release using M5 triangular key, available as accessory

## Ordering code

Product type description:  
AV 25(1)K(2)U-GB215

(1)

<b>L</b>	left-hand model
<b>R</b>	right-hand model

(2)

<b>X11,5</b>	X-dimension of the latching bolt = 11,5 mm
<b>X20</b>	X-dimension of the latching bolt = 20 mm
<b>X30</b>	X-dimension of the latching bolt = 30 mm
<b>X40</b>	X-dimension of the latching bolt = 40 mm
<b>X45</b>	X-dimension of the latching bolt = 45 mm


### Note:

U = interlock bevel on the underside  
GB215 = additional, front-side M8 mounting holes

Variants that differ from this are special versions.  
Availability on request.

## Pictures

### Product picture (catalogue individual photo)




ID: kav25f01

| 455.3 kB | .jpg | 352.778 x 200.025 mm - 1000 x 567 px - 72 dpi

| 30.7 kB | .png | 74.083 x 41.981 mm - 210 x 119 px - 72 dpi

## Images (miscellaneous)



ID: kav25m01

| 115.2 kB | .jpg | 352.778 x 206.022 mm - 1000 x 584 px - 72 dpi

## Assembly example



ID: kav--m03

| 23.5 kB | .cdr |

Schmersal Ltd., Sparrowhawk Close, WR14 1GL Malvern

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 24/08/2022, 10:35