Main

Mani		
Range of product	Harmony XVC4	
Product or component type	Complete pre-wired monolithic tower light	
Beacon or indicator bank unit type	3 illuminated units	
Sound signalling	Without	
Mounting diameter	40 mm	
Component name	XVC	
Device short name	XVC	
Light source	LED steady red LED steady orange LED steady green	
Supply circuit type	AC/DC	

Complementary

Complementary		
Material	Polycarbonate: illuminated unit ABS (acrylonitrile butadiene-styrene): base unit PBT + ABS (UL94HB): top cover SGP (chromium-plated): support tube	
Mounting location	On support tube, 17 mm	
Product mounting	On support tube, 17 mm	
[Us] rated supply voltage	24 V	
[Us] rated supply voltage	24 V	
Cable cross section	0.33 mm²	
AWG gauge	AWG 22	
Cable length	600 mm	
Marking	CE	
[Uimp] rated impulse withstand voltage	0.8 kV	
Current consumption	75 mA	
Flashing frequency	1 Hz	
Net weight	0.54 kg	
Height	473.5 mm	

Environment

EN/IEC 61000-6-3 EN/IEC 61000-6-2	
UL	
TC	
-3570 °C	
-1050 °C	
Class I conforming to EN/IEC 61140	
Class I conforming to EN/IEC 61140	
IP23 vertical surface installation conforming to EN/IEC 60529	
	TC -3570 °C -1050 °C Class I conforming to EN/IEC 61140 Class I conforming to EN/IEC 61140

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	754 g
Package 1 Height	6.8 cm
Package 1 width	6.8 cm
Package 1 Length	75.2 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	8.684 kg
Package 2 Height	17.5 cm
Package 2 width	37 cm
Package 2 Length	77.5 cm
Unit Type of Package 3	P06
Number of Units in Package 3	20
Package 3 Weight	25.368 kg
Package 3 Height	50 cm
Package 3 width	60 cm
Package 3 Length	80 cm

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End of Life Information	
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	

Contractual warranty

Product data sheet


XVC4B3

Dimensions Drawings

Pre-assembled and Pre-wired Tower Light with Support Tube Mounting

Dimensions

Below drawing shows the maximum configuration of the product. Select the number of stages according to the product characteristics in order to get **b** dimension.



No. of illuminated units	b Without buzzer (mm)	b Without buzzer (in.)
1 stage	403.50	15.89
2 stages	438.50	17.26
3 stages	473.50	18.64
4 stages	508.50	20.02
5 stages	543.50	21.40

Product data sheet

XVC4B3

Mounting and Clearance

Pre-assembled and Pre-wired Tower Light

Support Tube Mounting

