

# KSE363TPN



Products Low Voltage Products and Systems Enclosed Switches Enclosed Switch-Disconnectors

## General Information

<b>Extended Product Type:</b>	KSE363TPN
<b>Product ID:</b>	2CMA144580R1000
<b>EAN:</b>	7392696445801
<b>Catalog Description:</b>	KSE363TPN Enclosed Switch Disconnecter
<b>Long Description:</b>	Aluminum enclosed front operated switch-disconnectors, 3-pole, IP65. Enclosure in Aluminum alloy (Silumin) with metric threaded cable entries. Light grey box with dark grey cover. Operating handle in black BPT plastic. Delivery includes PE+neutral terminal and membrane glands (IP54) / sealing plugs. For IP65 degree of protection compression glands must be used. Interlocked cover.

## Additional Information

<b>ABB Industrial IT Suite:</b>	Control IT
<b>Cable Entry Position:</b>	Up/Down
<b>Cable Outlets Per Side:</b>	2xM40 / 2xM40+M16
<b>Cable Throughouts:</b>	40
<b>Conventional Free-air Thermal Current (<math>I_{th}</math>):</b>	63 A
<b>Conventional Thermal Current (<math>I_{the}</math>):</b>	Fully Enclosed 63 A
<b>Country of Origin:</b>	Bulgaria (BG)
<b>Customs Tariff Number:</b>	85365015
<b>Data Sheet, Technical Information:</b>	1SCC340009C0201
<b>Declaration of Conformity - CE:</b>	1SCC340062D2702
<b>Degree of Protection:</b>	acc. to IEC 60529 IP65
<b>E-number:</b>	44580
<b>EAN:</b>	7392696445801
<b>ETIM 4:</b>	EC000216 - Switch disconnecter
<b>ETIM 5:</b>	EC000216 - Switch disconnecter
<b>ETIM 6:</b>	EC000216 - Switch disconnecter
<b>Enclosure Material:</b>	Aluminium
<b>Environmental Information:</b>	2CMC300001D0135
<b>Gross Weight:</b>	1.75 kg
<b>Handle Type:</b>	Round handle
<b>IIT Publishing Status:</b>	Level 0 - Information enabled
<b>Industrial IT Certification Level:</b>	0
<b>Instructions and Manuals:</b>	1SCC340166M0202
<b>Invoice Description:</b>	KSE363TPN Enclosed Switch Disconnecter
<b>Minimum Order Quantity:</b>	1 piece
<b>Number of Poles:</b>	3
<b>Object Classification Code:</b>	Q 2CMT005069
<b>Package Level 1 EAN:</b>	7392696445801
<b>Package Level 1 Gross Weight:</b>	1.75 kg
<b>Package Level 1 Height:</b>	170 mm
<b>Package Level 1 Length:</b>	150 mm
<b>Package Level 1 Units:</b>	1 piece
<b>Package Level 1 Width:</b>	240 mm

<b>Product Main Type:</b>	KSE363
<b>Product Name:</b>	Enclosed Switch Disconnecter
<b>Product Net Depth:</b>	145 mm
<b>Product Net Height:</b>	230 mm
<b>Product Net Length:</b>	230 mm
<b>Product Net Weight:</b>	1.75 kg
<b>Product Net Width:</b>	160 mm
<b>Protection Type:</b>	Watertight
<b>Rated Current (I<sub>n</sub>):</b>	63 A
<b>Rated Insulation Voltage (U<sub>i</sub>):</b>	acc. to IEC/EN 60664-1 750 V
<b>Rated Operational Current AC-22A (I<sub>e</sub>):</b>	(380 ... 415 V) 63 A (690 V) 63 A
<b>Rated Operational Power AC-23A (P<sub>e</sub>):</b>	(500 V) 22 kW (690 V) 15 kW (400 V) 22 kW
<b>Rated Operational Voltage:</b>	Main Circuit 750 V
<b>RoHS Date:</b>	2009-01
<b>RoHS Information:</b>	2CMC300025D0001
<b>Selling Unit of Measure:</b>	piece
<b>Short Description:</b>	Enclosed Safety Switches, KSE 363 TPN
<b>Size:</b>	160X230X145
<b>Standards:</b>	IEC 60 947-3
<b>Suitable For:</b>	KSE
<b>Suitable for Product Class:</b>	KSE
<b>UNSPSC:</b>	39120000
<b>Maximum Mounted Auxiliary Contacts:</b>	1 NO, 0 NC
<b>Handle Color:</b>	Black

