



### Main

Range	Acti 9
Product name	Acti 9 Isobar P A
Product or component type	Distribution board
Device application	Distribution
Enclosure type	Standard
Door type	Overall
Provided equipment	Door Enclosure Earth terminal block Neutral terminal block Earth stud Blanking plate Front cover Pan assembly
Colour	Cream (RAL 9001)

### Complementary

Enclosure mounting	Surface
Poles description	1P + N
[Ie] rated operational current	125 A 230/240 V AC
Breaking capacity	25 kA
Overvoltage category	IV
[Ui] rated insulation voltage	500 V
[Uimp] rated impulse withstand voltage	6 kV
Incomer device options	Switch disconnecter 2P Terminal block 2P RCCB 2P
Protection device options at outgoer	Miniature circuit breaker (MCB) 63 A max Residual current circuit breaker with overcurrent protection (RCBO) 45 A max 100 mA max Residual current circuit breaker with overcurrent protection (RCBO PoN) 45 A max 100 mA max
Number of ways	2 ways as outgoer - 1P
Enclosure material	Steel
Surface treatment	Epoxy
Surface finish	Powder paint

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Height	300 mm
Width	200 mm
Depth	117 mm
Product weight	1.8 kg

## Environment

IP degree of protection	IP3x external conforming to BS EN 60529 IP20 internal conforming to BS EN 60529
IK degree of protection	IK05
Pollution degree	3
Ambient air temperature for operation	-35...70 °C
Ambient air temperature for storage	-40...80 °C

## Offer Sustainability

Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations