# For Use With 2B4\*\*\* Metal Operating Heads

## 3/2 Valve Bodies with Mounting Ring







Connections	Function	Type of switching*	Part number
5/32" Instant	3/2	NNP	PXBB3111B
5/32" Instant	3/2	NP	PXBB3121B
5/32" Instant	3/2	Universal 3 way	PXBB4131B

NNP: Normally non-passing.

Note: Mount up to 3 valves on mounting ring for push buttons.

Mount up to 2 valves on mounting ring for selector switches, valves cannot be mounted in center position.

### **Additional Valve Bodies**







Connections	Function	Type of switching*	Part number
5/32" instant straight	3/2	NNP	PXBB3911
5/32" instant swivel	3/2	ININP	PXBB3912
5/32" instant straight	3/2	NP	PXBB3921
5/32" instant swivel	3/2	NP	PXBB3922
5/32" instant straight	3/2	Universal	PXBB4931
5/32" instant swivel	3/2	3 way	PXBB4932

<sup>\*</sup> NNP: Normally non-passing.

#### For Push Buttons and Visual Indicators

### Legend Plates for PXBB Devices (22mm)

	Description			Part number
Without tex	t for customer eng	raving		
	Black / red back	ground (white letter	rs)	ZBY2101
	Yellow / white ba	ckground (black le	tters)	ZBY4101
With text fo	r push buttons			
	Start			ZBY2303
	Stop			ZBY2304
	Forward			ZBY2305
	Reverse			ZBY2306
	Up			ZBY2307
	Down			ZBY2308
	Right			ZBY2309
	Left			ZBY2310
	On			ZBY2311
	Off			ZBY2312
	Open			ZBY2313
	Close			ZBY2314
	Inch			ZBY2321
	Reset			ZBY2323
	Power On			ZBY2326
	Slow			ZBY2327
	Fast			ZBY2328
	Emergency stop			ZBY2330
	Run			ZBY2334
Vith text fo	r 2 position select	ors		
		Off	On	ZBY2367
With text fo	r 3 position select	ors		
	Hand	Off	Auto	ZBY2387

# **Blank Legend Plates for Inscription**

For PXBB devices (2 lines of 11 characters maximum)

Please indicate the required text when ordering.

(Allow 3 weeks for delivery)

Description	Part number
Black background / White letters	ZBY2002

#### For 22mm Visual Indicators Only

2 lines of 11 characters maximum

Please indicate the required text when ordering.

(Allow 3 weeks for delivery)

Description	Part number
Black background / white letters	ZB2BY2002

#### **Electrical Switch Bodies**

When combined with pneumatic valves ,these contact blocks allow different forms of power to be provided from a single push button. Can be mounted with both types of valves PXBB3 / PXBB4.

	Type of contact	Part number
	Normally open (NO)	ZBE101
1	Normally closed (NC)	ZBE102

Note: Plastic mounting ring ZB5AZ009 to be used with ZB5 plastic operating heads. Metal mounting ring ZB4BZ009 to be used with ZB4 metal operating heads.

Electrical specification: 240V, 10Amp

D238

