

General Information

Extended Product Type:	KSF425TPSN
Product ID:	2CMA142437R1000
EAN:	7392696424370
Catalog Description:	KSF425TPSN Fireman switch
Long Description:	Firemans switch, 4-pole, side operated in aluminum.Red painted switch-disconnectors for use by firemen to disconnect in case of fire.Enclosure in Aluminum alloy(Silumin) with metric threaded cable entries and special operating handle with loop and interlocking mechanism. Delivery includes PE terminal and membrane glands(IP54) / sealing plugs. For IP65 degree of protection compression glands must be used.

Categories

Products » Low Voltage Products and Systems » Enclosed Switches » Enclosed Switch-Disconnectors

Ordering

Minimum Order Quantity:	1 piece
Customs Tariff Number:	85365015

Popular Downloads

Data Sheet, Technical Information:	1SCC340009C0201
Instructions and Manuals:	2CMC300004D0001

Dimensions

Product Net Width:	111 mm
Product Net Height:	130 mm
Product Net Depth:	60 mm
Product Net Weight:	0.59 kg

Technical

Rated Operational Current AC-22A (I _e):	(380 ... 415 V) 25 A (500 V) 25 A (690 V) 25 A
Rated Operational Current AC-23A (I _e):	(380 ... 415 V) 25 A
Rated Operational Power AC-23A (P _e):	(380 ... 415 V) 7.5 kW
Conventional Free-air Thermal Current (I _{th}):	32 A
Rated Insulation Voltage (U _i):	690 V
Handle Color:	Black
Handle Type:	Side-operated handle
Standards:	IEC 60947-1,-3
Number of Poles:	4
Cable Entry Position:	Up/Down
Cable Outlets Per Side:	2xM25/2xM25
Cable Throughouts:	25
Degree of Protection:	IP65
Enclosure Material:	Aluminium

Environmental

RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2008 Q1
Environmental Information:	2CMC300001D0089

Certificates and Declarations (Document Number)

Declaration of Conformity - CE:	2CMC300009
RoHS Information:	2CMC300025D0001

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	62 mm
Package Level 1 Length:	131 mm
Package Level 1 Height:	112 mm

Package Level 1 Gross Weight: 0.59 kg

Package Level 1 EAN: 7392696424370

Classifications

Object Classification Code: Q
2CMT005069

ETIM 4: EC000216 - Switch disconnecter

ETIM 5: EC000216 - Switch disconnecter

UNSPSC: 39120000

